

SEI5633D



Product Family

Built-in type

Dimensions

Power supply

Type

EAN code

Hob


Ultra-low profile or Fully Flushed

60 cm

Electric

Induction

8017709350468



Aesthetics

Aesthetic

Colour

Finishing

Material

Glass type

Glass edge

Gas_replacement

Type of control setting

LED colours

Control knob position

Logo

Serigraphy colour

Universale

Black

Glass

Glass

Ceramic

Straight edge

Yes

Penta

Red

Front

Silk screen

Grey

Program / Functions



No. of induction cook zones

3

Time-setting options

Spegnimento automatico

No. of cooking zones with booster

3

Main on/off switch

Yes

Power levels

12

Total no. of cook zones

3

Options



Worktop Cut-Out	478-482x555-560 mm	Residual time indicator	Yes
End cooking timer	3	Limited Power	Yes
Minute minder	1	Consumption Mode	
End of cooking alarm	Yes	Control Lock / Child Safety	Yes

Technical Features



Centre-left - Induction - Single - 2.70 kW - Booster 3.60 kW - Ø 28.0 cm


Rear-right - Induction - Single - 1.50 kW - Booster 2.00 kW - Ø 21.0 cm

Front-right - Induction - Single - 1.20 kW - Booster 1.60 kW - Ø 15.0 cm

Automatic setting according to pan dimension	Yes	Automatic switch off when overheated	Yes
pan detection	Yes, min. 9 cm	Residual heat indicator	Yes
Minimum pan diameter indication	Yes	Protection against accidental start up	Yes

Electrical Connection

Electrical connection rating (W)	7200 W	Additional connection modalities	Yes, Double and Three Phase
Current	32 A	Frequency (Hz)	50/60 Hz
Voltage (V)	220-240 V	Power supply cable length	120 cm
Voltage 2 (V)	380-415 V	Plug	Not present
Type of electric cable installed	Yes, Single phase		



Compatible Accessories



SCRP

Non-scratch hob scraper - suitable for induction and ceramic hobs

Symbols glossary

	Power booster: option allows the zone to work at full power when very intense cooking is necessary.		Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.
	CUT_OUT_STANDARD_72dpi		ECO-logic: option allows you to restrict the power limit of the appliance real energy saving.
	Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.		Induction: The work of these hobs is based on the principle of electromagnetic induction. The heat is generated directly in the bottom of the pan during its contact with the hob.
	Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.		Time elapsed: shows how long the cooking zone has been in use.
	Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time.		Min diameter pot detection of 9 cm