

# SEU122B





Product family Cooktop

**Installation** Ultra-low profile

Dimensions 12"
Power supply Electric
Type Ceramic

**EAN code** 8017709240929



#### **Aesthetic**



AestheticsUniversalColorBlackFinishingGlassMaterialGlassGlassCeramicGlass edgeBeveledControl setting typeTouch controls

Controls positionFrontSilkscreen colorGray

#### **Technical Features**







Front-center - Ceramic - single - 1.00 kW - Ø 14.8 cm Rear-center - Ceramic - single - 1.40 kW - Ø 18.4 cm

Automatic switch-off in Yes

case of over-heating

Automatic switch-off in Yes

case of overflow

Residual heat indicator Yes

#### **Electrical Connection**

Nominal power 2400 W Current 22 A Type of electric cable

supplied

Yes, Single phase

Frequency 60 Hz




Voltage

Electric cable type

120 V

Single phase

Power cord length Terminal box 47 1/4 " 3 poles





## Not included accessories



**SCRP** 

Induction and ceramic hobs and teppanyaki scraper



### Symbols glossary (TT)



Power booster: option allows the zone to work at full power when very intense cooking is necessary.



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.



Glass ceramic: The base of the hob is made glass ceramic. Heating is performed by the heating elements Hi-Light.



Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids.



Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.



Touch control