

SEU122B





Product family Cooktop

Installation Ultra-low profile

Dimensions 12"
Power supply Electric
Type Ceramic

EAN code 8017709240929



Aesthetic



AestheticsUniversalColorBlackFinishingGlassMaterialGlassGlassCeramicGlass edgeBeveledControl setting typeTouch controls

Controls positionFrontSilkscreen colorGray

Programs / Functions



No. of ceramic cook zones2Cooking zones with Booster2Power levels9Cooking zones2

Technical Features







Front-center - Ceramic - single - 1.00 kW - Ø 14.8 cm Rear-center - Ceramic - single - 1.40 kW - Ø 18.4 cm

Residual heat indicator Yes



Automatic switch-off in Yes case of over-heating


Automatic switch-off in Yes case of overflow

Electrical Connection

Nominal power 2400 W Type of electric cable Yes, Single phase

Current 22 A supplied

Voltage 120 V Frequency 60 Hz
Electric cable type Single phase Power cord length 47 1/4 "
Terminal box 3 poles





Not included accessories



SCRP

Induction and ceramic hobs and teppanyaki scraper



Symbols glossary (TT)



Power booster: option allows the zone to work at full power when very intense cooking is necessary.



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Touch control



Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.



Glass ceramic: The base of the hob is made glass ceramic. Heating is performed by the heating elements Hi-Light.



Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids.

