SEU365ETB

Product family	Cooktop
Installation	Ultra-low profile
Dimensions	36"
Power supply	Electric
Type	Ceramic
EAN code	8017709241001



Aesthetic

Color	Black
Finishing	Glass
Material	Glass
Glass	Ceramic
Glass edge	Beveled
Control setting type	Touch controls
Controls position	Front
Logo	Silkscreened
Silkscreen color	Gray

Program / Functions

No. of ceramic cook zones	5
Cooking zones with Booster	5
Power levels	9
Cooking zones	5

Options

End cooking timer	1	**Limited Power Consumption Mode in W**	4000 W
End-of-cooking acoustic alarm	Yes	**Showroom mode**	Yes

Residual time indicator	Yes	**Child safety lock**	Yes
Limited power consumption option	Yes	**Quick start**	Yes

Technical Features

Front-left - Ceramic - single - 1.20 kW - Ø 14.8 cm
Rear-left - Ceramic - double - 0.75 - 1.80 kW - Ø 12.4 - Ø 18.4 cm
Center - Ceramic - Triple - 1.05 - 1.95 - 2.70 kW - Ø 15.0 - Ø 21.6 - Ø 28.8 cm
Rear-right - Ceramic - single - 1.80 kW - Ø 18.4 cm
Front-right - Ceramic - single - 1.20 kW - Ø 14.8 cm

Automatic switch-off in case of over-heating	Yes	**Residual heat indicator**	Yes
Automatic switch-off in case of overflow	Yes		

Electrical Connection

Nominal power	8700 W	**Frequency**	60 Hz
Current	25 A	**Power cord length**	47 1/4 "
Voltage	240 V	**Terminal box**	6 poles
Voltage 2 (V)	208 V	**Plug**	No
Electric cable type	Single phase		



Compatible Accessories



SCRP

Induction and ceramic hobs and teppanyaki scraper

Symbols glossary



Power booster: option allows the zone to work at full power when very intense cooking is necessary.



Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.



ECO-logic: option allows you to restrict the power limit of the appliance real energy saving.



Glass ceramic: The base of the hob is made glass ceramic. Heating is performed by the heating elements Hi-Light.



Quick Start function: the chosen temperature is reached faster. The heating element works at maximum power until the right temperature is reached.



Time elapsed: shows how long the cooking zone has been in use.



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Touch control



Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.



Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids.



Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.



Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time.