

SHU671X

Product family Hood

Hood Type Integrated hood

Design Ceiling
Extraction Recirculation
Material Stainless steel
Type of steel Brushed

EAN code 8017709336493

Aesthetic Universale
Colour Stainless steel

Finishing Satin



Controls

Control setting Buttons

Program / Functions

No. of speeds Intensive speed 3 BOOST

Technical Features





Motor power

No. of lights 2 No. of filters 2

Light type LED Anti-grease filters Stainless steel

Light Power 1.1 W Vent outlet 150 mm Light color temperature 4000 K Minimum distance from 650 mm

scale (K) GAS hob

250 W

Free outlet maximum 770 m³/h Minimum distance from 600 mm

capacity ELECTRIC hob

| | Extraction rate IEC 61591 [m³/h] | Noise level IEC 60704- 2-13 [dBA] |
|---------|-------------------------------------|--------------------------------------|
| Speed 1 | 300 | 46 |
| Speed 2 | 450 | 55 |
| Speed 3 | 620 | 62 |



| Intensive speed | 740 | 66 |
|-----------------|-----|----|
|-----------------|-----|----|

Accessories Included

Tube reduction Yes

Electrical Connection

Electrical connection 252 W

rating

Current 10 A

Voltage 220-240 V


Frequency (Hz)
Power supply cable


length


Plug


50-60 Hz 1500 mm

(I) Australia











Compatible Accessories

KITFC152

Charcoal filters Round Kit 2 pieces





Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.