

# **SHU671X**

Product family Hood

Hood Type Integrated hood

Design Ceiling
Extraction Recirculation
Material Stainless steel
Type of steel Brushed

EAN code 8017709336493

Aesthetic Universale
Colour Stainless steel

Finishing Satin



#### **Controls**

Control setting Buttons

### **Program / Functions**

No. of speeds Intensive speed 3 BOOST

#### **Technical Features**





No. of lights 2 No. of filters 2

Light type LED Anti-grease filters Stainless steel

Light Power 1.1 W Vent outlet 150 mm Light color temperature 4000 K Minimum distance from 650 mm

scale (K) GAS hob

Free outlet maximum 770 m³/h Minimum distance from 600 mm

capacity ELECTRIC hob

Motor power 250 W

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	300	46
Speed 2	450	55
Speed 3	620	62



Intensive speed	740	66
-----------------	-----	----

### **Accessories Included**

Tube reduction Yes

#### **Electrical Connection**

Electrical connection 252 W

rating

Current 10 A

Voltage 220-240 V

Frequency (Hz)
Power supply cable


length Plug


ngth


(I) Australia


50-60 Hz

1500 mm











# **Compatible Accessories**

#### KITFC152

Charcoal filters Round Kit 2 pieces





## Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.