

SHU921X

Product family Hood

Hood Type Integrated hood

DesignCeilingExtractionExtractionMaterialStainless steelType of steelBrushed

EAN code 8017709346041
Colour Stainless steel

Finishing Satin
Serigraphy colour Black
Logo Applied

Controls

Control setting Buttons Led color White

Program / Functions

No. of speeds
Intensive speed

Technical Features



No. of lights 2 No. of filters 2

Light type LED Anti-grease filters Stainless steel

Light color temperature 4000 K Vent outlet 150 mm scale (K) Minimum distance from 650 mm

Free outlet maximum 780 m³/h GAS hob

capacity Minimum distance from 600 mm

Motor power 250 W ELECTRIC hob

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	300	46
Speed 2	450	55
Speed 3	630	62



Intensive speed	750	66
-----------------	-----	----

Accessories Included

Tube reduction Yes

Electrical Connection

Electrical connection 252 W

rating

Current 10 A

Voltage 220-240 V


Frequency (Hz)
Power supply cable


length


Plug


50-60 Hz 1500 mm

(I) Australia











Compatible Accessories

KITFC152

Charcoal filters Round Kit 2 pieces





Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.