

SHW910X2

Product family Hood Type Design Extraction Material Type of steel EAN code Aesthetic Colour Logo Hood Decorative wall hood Chimney Recirculation Stainless steel Brushed 8017709346164 Universale Stainless steel Embossed



Controls

Control setting

Buttons

Program / Functions

No. of speeds Intensive speed

3 BOOST

Technical Features

No. of lights	2
Light type	LED
Light Power	1 W
Light color temperature scale (°K)	4000 °K
Free outlet maximum capacity	1000 m³/h
Motor power	340 W

No. of filters	3
Anti-grease filters	Stainless steel
Vent outlet	150 mm
Minimum distance from GAS hob	650 mm
Minimum distance from ELECTRIC hob	600 mm

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	400	56
Speed 2	610	66
Speed 3	810	72



Intensive speed	940	75		
Accessorie	s Included			
Tube reduction	Yes			
Tube reduction				
		Frequency (Hz)	50-60 Hz	
Electrical C	onnection	Frequency (Hz) Power supply cable	50-60 Hz 1500 mm	

Optional accessories

Yes

Charcoal filter



Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.