

SI1B2642D



Product Family	Hob
Built-in type	Ultra-low profile or Fully Flushed
Dimensions	60 cm
Power supply	Electric
Type	Induction
EAN code	8017709339685



Aesthetics



Aesthetic	Universale
Colour	Black
Finishing	Glass
Material	Glass
Glass type	Ceramic
Glass edge	Straight edge
Type of control setting	Digi Touch
LED colours	Red
Control knob position	Front
Logo	Silk screen
Serigraphy colour	Grey

Program / Functions



No. of induction cook zones	4
Time-setting options	Spegnimento automatico
No. of cooking zones with booster	4
No. of Flexible zones	2
Main on/off switch	Yes
Power levels	9
Total no. of cook zones	4

Options



Flexible Zone Type	Bridge	Residual time indicator	Yes
Worktop Cut-Out	478-482x555-560 mm	Limited Power	Yes
End cooking timer	4	Consumption Mode	
Minute minder	1	Control Lock / Child Safety	Yes
End of cooking alarm	Yes	Bridge option	Yes

Technical Features



Front-left - Induction - Single - 1.50 kW - Booster 2.00 kW - Ø 18.0 cm

Rear-left - Induction - Single - 1.50 kW - Booster 2.00 kW - Ø 18.0 cm


Rear-right - Induction - Single - 1.50 kW - Booster 2.00 kW - Ø 21.0 cm

Front-right - Induction - Single - 1.20 kW - Booster 1.60 kW - Ø 14.5 cm

Left Bridge dimension	38.5x18.0 cm	Minimum pan diameter indication	Yes
Booster power right Bridge		Automatic switch off when overheat	Yes
Automatic setting according to pan dimension	Yes	Residual heat indicator	Yes
pan detection	Yes, min. 9 cm	Protection against accidental start up	Yes

Electrical Connection

Electrical connection rating (W)	7200 W	Additional connection modalities	Yes, Double and Three Phase
Current	32 A	Frequency (Hz)	50/60 Hz
Voltage (V)	220-240 V	Power supply cable length	120 cm
Voltage 2 (V)	380-415 V	Plug	Not present
Type of electric cable installed	Yes, Single phase		















Compatible Accessories



SCRP

Non-scratch hob scraper - suitable for induction and ceramic hobs

Symbols glossary

	Power booster: option allows the zone to work at full power when very intense cooking is necessary.		Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.
	Touch control		CUT_OUT_STANDARD_72dpi
	ECO-logic: option allows you to restrict the power limit of the appliance real energy saving.		Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.
	Induction: The work of these hobs is based on the principle of electromagnetic induction. The heat is generated directly in the bottom of the pan during its contact with the hob.		Min diameter pot detection of 9 cm
	Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.		Time elapsed: shows how long the cooking zone has been in use.
	Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time.		TWIN_ZONE_72dpi