

SI1M4734D

**Product Family**

Hob

Built-in type

Ultra-low profile or Fully Flushed

Dimensions

72 cm

Power supply

Electric

Type

Induction

EAN code

8017709338800



Aesthetics

**Aesthetic**

Classica

Colour

Black

Finishing

Glass

Material

Glass

Glass type

Ceramic

Glass edge

Straight edge

Type of control setting

Compact Slider Plus

Slider

Yes

LED colours

Red

Control knob position

Front

Logo

Silk screen

Serigraphy colour

Grey

Program / Functions

**No. of induction cook zones**

3

Time-setting options

Spegnimento automatico

No. of cooking zones with booster

3

No. of Flexible zones

1

Main on/off switch

Yes

Power levels

9

Auto-vent 2.0

Yes

Total no. of cook zones

3

Options

																							
Multizone Option	Yes																						Yes
Flexible Zone Type	MultiZone																						Yes
Worktop Cut-Out	478-482x555-560 mm																						Si Advance
Auto Multizone	Yes																						Consumption Mode
Double Booster	Yes																						2400 a 7400 - step 100 W
Keep warm automatic function	Yes																						Consumption Mode in W
Grill function	Yes																						Showroom Demo Option
End cooking timer	3																						Safety
Pause option	Yes																						Cleaning option
Minute minder	1																						Quick start
																							Rapid level selection

Technical Features



Front-left - Induction - Multizone - 2.10 kW - Booster 2.50 kW - 21.0x19.0 cm

Rear-left - Induction - Multizone - 2.10 kW - Booster 2.50 kW - 21.0x19.0 cm


Right - Induction - Single - 2.30 kW - Booster 3.00 kW - Double booster 3 kW - Ø 25.0 cm

Multizone left - Booster 3.7 kW - 38.5x23.0 cm

Left Bridge dimension	39.5x22.0 cm	Automatic switch off when overflow	Yes
Automatic setting according to pan dimension	Yes	Residual heat indicator	Yes
pan detection	Yes, min. 9 cm	Eco-Heat	Yes
Permanent Automatic Pot Detection with indication of the relative control	Yes	Protection against accidental start up	Yes
Automatic switch off when overheat	Yes		

Electrical Connection

Electrical connection rating (W)	6700 W	Additional connection modalities	Yes, Double and Three Phase
Current	30 A	Frequency (Hz)	50/60 Hz
Voltage (V)	220-240 V	Power supply cable length	120 cm
Voltage 2 (V)	380-415 V	Terminal box	5 poles
Type of electric cable installed	Yes, Single phase	Plug	Not present



Compatible Accessories



GRILLPLATE

Universal griddle for induction, gas, ceramic and electric hobs. Non-stick surface ideal for cooking meat, cheese and vegetables. Dimensions: 410 x 240 mm.



SCRP

Non-scratch hob scraper - suitable for induction and ceramic hobs



TPKPLATE

Universal plate for induction, gas, ceramic and electric hobs. Non-stick surface ideal for cooking fish, eggs and vegetables. Dimensions: 410 X 240 mm.

Symbols glossary

	Automatic merge of zones for a bigger area		Permanent auto pot detection
	Connection between hob and hood		Power booster: option allows the zone to work at full power when very intense cooking is necessary.
	Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.		Compact Slider back-lighted ghost effect
	The slider control panel allows you to adjust the power simply by passing your finger across the touch device.		CUT_OUT_STANDARD_72dpi
	Additional maximum power level for a better energy consumption		Eco-Heat: this function warns when the zone is still hot after being switched off. As well as ensuring maximum safety by preventing burns, this also allows you to make use of residual heat to continue cooking or keep foods hot.
	Grill function		This function allows you to keep cooked food warm without burner it
	Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.		Induction: The work of these hobs is based on the principle of electromagnetic induction. The heat is generated directly in the bottom of the pan during its contact with the hob.
	Multizone: allows several pans to be used at once, large or small, offering freedom of placement and greater flexibility		Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids.
	Min diameter pot detection of 9 cm		All cooking zones can be reduced to the minimum power level, so the hob can be left unattended for a short period without food overcooking or burning. Then just press again this function, the previously set power levels can be reactivated.
	Possibility to set the maximum power absorption of the hob		Quick selection, with one touch cooking begins at the highest level, then automatically reduces after time. Ideal for dishes that require quick boiling and then continued cooking without constant control (eg beef broth).
	Quick Start function: the chosen temperature is reached faster. The heating element works at maximum power until the right temperature is reached.		Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 °C, the indicator goes out.
	Time elapsed: shows how long the cooking zone has been in use.		Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time.