SI4742D

Product Family	Hob
Built-in type	Ultra-low profile or Fully Flushed
Dimensions	70/75 cm
Power supply	Electric
Type	Induction
EAN code	8017709288150



Aesthetics

Aesthetic	Universale
Colour	Black
Finishing	Glass
Material	Glass
Glass type	Ceramic
Glass edge	Straight edge
Type of control setting	Compact Slider
Slider	Yes
LED colours	Red
Control knob position	Front
Logo	Silk screen
Serigraphy colour	Grey

Program / Functions

No. of induction cook zones	4
Time-setting options	Automatic switch-off
No. of cooking zones with booster	4
Main on/off switch	Yes
Power levels	9
Total no. of cook zones	4

Options

Worktop Cut-Out	478-482x555-560 mm
Keep warm automatic function	Yes
End cooking timer	4
Minute minder	4
End of cooking alarm	Yes
Residual time indicator	Yes
Limited Power Consumption Mode	Si Advance
Limited Power Consumption Mode in W	2400, 2800, 3500, 4000, 4500, 5000, 5500, 6000, 7400 W
Control Lock / Child Safety	Yes
Rapid level selection	Yes


Technical Features

Front-left - Induction - Single - 2.30 kW - Booster 3.00 kW - Ø 21.0 cm
Rear-left - Induction - Single - 1.85 kW - Booster 2.10 kW - Ø 16.0 cm
Rear-right - Induction - Single - 2.30 kW - Booster 3.00 kW - Ø 21.0 cm
Front-right - Induction - Single - 1.85 kW - Booster 2.10 kW - Ø 16.0 cm

Automatic setting according to pan dimension	Yes
pan detection	Yes, min. 7 cm
Permanent Automatic Pot Detection with indication of the relative control	Yes
Minimum pan diameter indication	Yes
Automatic switch off when overheat	Yes
Residual heat indicator	Yes
Protection against accidental start up	Yes

Electrical Connection

Electrical connection rating (W)	7400 W
Current	33 A
Voltage (V)	220-240 V
Voltage 2 (V)	380-415 V
Type of electric cable installed	Yes, Single phase
Additional connection modalities	Yes, Double and Three Phase
Frequency (Hz)	50/60 Hz
Power supply cable length	120 cm
Terminal box	6 poles
Plug	Not present


220
147
510
750
478-482
min.50
max.R5
555-560
min.20
50

Compatible Accessories



SCRP

Non-scratch hob scraper - suitable for induction and ceramic hobs

Symbols glossary



Permanent auto pot detection



Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.



CUT_OUT_STANDARD_72dpi



Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.



Quick selection, with one touch cooking begins at the highest level, then automatically reduces after time. Ideal for dishes that require quick boiling and then continued cooking without constant control (eg beef broth).



Time elapsed: shows how long the cooking zone has been in use.



Min diameter pot detection of 7 cm.



Compact Slider intuitive and easy to use



Power booster: option allows the zone to work at full power when very intense cooking is necessary.



The slider control panel allows you to adjust the power simply by passing your finger across the touch device.



This function allows you to keep cooked food warm without burner it



Induction: The work of these hobs is based on the principle of electromagnetic induction. The heat is generated directly in the bottom of the pan during its contact with the hob.



Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.



Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time.



Possibility to set the maximum power absorbion of the hob.