
# SI5633D

| | |
|---|---|
| **Product Family** | Hob |
| **Built-in type** | Ultra-low profile or Fully Flushed |
| **Dimensions** | 60 cm |
| **Power supply** | Electric |
| **Type** | Induction |
| **EAN code** | 8017709348861 |



## Aesthetics

| | |
|---|---|
| **Aesthetic** | Universale |
| **Colour** | Black |
| **Finishing** | Glass |
| **Material** | Glass |
| **Glass type** | Ceramic |
| **Glass edge** | Straight edge |
| **Gas_replacement** | Yes |
| **Type of control setting** | Penta |
| **LED colours** | Red |
| **Control knob position** | Front |
| **Logo** | Silk screen |
| **Serigraphy colour** | Grey |

## Program / Functions

| | |
|---|---|
| **No. of induction cook zones** | 3 |
| **Time-setting options** | Automatic switch-off |
| **No. of cooking zones with booster** | 3 |
| **Main on/off switch** | Yes |
| **Power levels** | 12 |
| **Total no. of cook zones** | 3 |

## Options

| | | | |
|---|---|---|---|
| **Worktop Cut-Out** | 478-482x555-560 mm | **Residual time indicator** | Yes |
| **End cooking timer** | 3 | **Limited Power Consumption Mode** | Yes |
| **Minute minder** | 1 | **Control Lock / Child Safety** | Yes |
| **End of cooking alarm** | Yes | | |


## Technical Features

Centre-left - Induction - Single - 2.70 kW - Booster 3.60 kW - Ø 28.0 cm
Rear-right - Induction - Single - 1.50 kW - Booster 2.00 kW - Ø 21.0 cm
Front-right - Induction - Single - 1.20 kW - Booster 1.60 kW - Ø 15.0 cm

| | | | |
|---|---|---|---|
| **Automatic setting according to pan dimension** | Yes | **Automatic switch off when overheat** | Yes |
| | | **Residual heat indicator** | Yes |
| **pan detection** | Yes, min. 9 cm | **Protection against accidental start up** | Yes |
| **Minimum pan diameter indication** | Yes | | |

## Electrical Connection

| | | | |
|---|---|---|---|
| **Electrical connection rating (W)** | 7200 W | **Additional connection modalities** | Yes, Double and Three Phase |
| **Current** | 32 A | **Frequency (Hz)** | 50/60 Hz |
| **Voltage (V)** | 220-240 V | **Power supply cable length** | 120 cm |
| **Voltage 2 (V)** | 380-415 V | **Plug** | Not present |
| **Type of electric cable installed** | Yes, Single phase | | |



## Compatible Accessories



**GRILLPLATE**

Universal griddle for induction, gas, ceramic and electric hobs. Non-stick surface ideal for cooking meat, cheese and vegetables. Dimensions: 410 x 240 mm.



**TPKPLATE**

Universal plate for induction, gas, ceramic and electric hobs. Non-stick surface ideal for cooking fish, eggs and vegetables. Dimensions: 410 X 240 mm.



**SCRP**

Non-scratch hob scraper - suitable for induction and ceramic hobs

## Symbols glossary



Power booster: option allows the zone to work at full power when very intense cooking is necessary.



CUT_OUT_STANDARD_72dpi



Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.



Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.



Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time.



Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.



ECO-logic: option allows you to restrict the power limit of the appliance real energy saving.



Induction: The work of these hobs is based on the principle of electromagnetic induction. The heat is generated directly in the bottom of the pan during its contact with the hob.



Time elapsed: shows how long the cooking zone has been in use.



Min diameter pot detection of 9 cm.