SISL7955X

Familie	Kookplaat
Inbouw	Tussenbouw
Afmeting	90 cm
Voeding	Elektrisch
Type	Inductie
EAN-code	8017709357177



Design

Esthetiek	Isola
Serie	Alta Pro
Kleur	Black with stainless steel effect frame
Perimeter lighting	Yes
Light color temperature scale (K)	4000 K
Afwerking	Glas
Materiaal	Glas
Type glas	Prestige ceramic
Glazen rand	Rechte rand
Kader	Ja
Kleur kader	Roestvrij staal
Frame material	Aluminum
Type bediening	Vivo Screen
Slider	TFT
Positie bediening	Voor
Logo	Geëtst
Kleur serigrafie	Grijs
Andere beschikbare kleuren	Zwart

Program / Functions

Aantal inductiekookzones	5
Opties tijdprogrammering	Automatische uitschakeling
Aantal kookzones met booster	5
Aantal Multizones	2
Hoofdtoets aan/uit	Ja

Vermogenniveaus	17
Totaal aantal kookzones	5

Opties



Multizone optie	Ja
Flexible Zone Type	MultiZone
Worktop Cut-Out	490x860 mm
Multizone optie	Ja
Multizone optie	Ja
Pasta function	Yes
Steaming function	Yes
Roasting function	Yes
Functie automatisch koken	Ja
Sudderfunctie	Ja
Warmhoudfunctie	Ja
Smelt/ Lage temperatuurfunctie	Ja
Automatische uitschakeling	5
Pauze optie	Ja
Timer	1
Akoestisch signaal einde kooktijd	Ja
Resttijd indicator	Ja
ECO-Logic optie	Ja, Advance
ECO-Logic optie - stappen	2400 a 11100 - step 100 W
Showroom demo optie	Ja
Kinderbeveiliging	Ja
Quick start	Ja
Snelle selectie niveaus	Ja

Technische specificaties



Linksvoor - Inductie - Multizone - 2.10 kW - Booster 3.00 kW - Double booster 3.70 kW - 21.0x18.0 cm
Linksachter - Inductie - Multizone - 2.10 kW - Booster 3.00 kW - Double booster 3.70 kW - 21.0x18.0 cm
Middenvoor - Inductie - enkel - 2.60 kW - Booster 4.00 kW - Double booster 5.50 kW - 26.0x18.0 cm
Rechtsachter - Inductie - Multizone - 2.10 kW - Booster 3.00 kW - Double booster 3.70 kW - 21.0x18.0 cm


Rechtsvoor - Inductie - Multizone - 2.10 kW - Booster 3.00 kW - Double booster 3.70 kW - 21.0x18.0 cm
Multizone left - Booster 3.70 kW - 36x21 cm
Multizone right - Booster 3.70 kW - 36x21 cm

Automatische herkenning panafmeting	Ja
Automatische panherkenning	minimaal 9 cm
Permanente automatische pandetectie met indicatie van de relatieve controle	Ja
Automatische stop bij oververhitting	Ja
Automatisch uitschakelen i.g.v. overkoken	Ja
Restwarmte indicator	Ja
beveiliging tegen onbedoeld inschakeling	Ja

Elektrische aansluiting

Aansluitwaarde	11100 W
Stroom	49 A
Spanning (V)	220-240 V
Spanning 2 (V)	380-415 V
Type of electric cable supplied	Yes, Single and Double phase
Frequentie	50/60 Hz
Lengte voedingskabel	120 cm

Type stroomkabel	Driefasig	**Connection box**	5 polig
Type stroomkabel	Enkele en dubbele fase	**Stekker**	Nee



Compatibele Accessoires



GRILLPLATE

Universal griddle for induction, gas, ceramic and electric hobs. Non-stick surface ideal for cooking meat, cheese and vegetables. Dimensions: 410 x 240 mm.



TPKPLATE

Universal plate for induction, gas, ceramic and electric hobs. Non-stick surface ideal for cooking fish, eggs and vegetables. Dimensions: 410 X 240 mm.



SCRP

Inductie- en keramische kookplaten en teppanyaki-schraper

Alternative products



SISL7955MB

Kleur: Black with matt black frame

Symbols glossary



Permanent auto pot detection



Powerbooster: optie zorgt ervoor dat de zone op vol vermogen werkt wanneer zeer intensief koken nodig is.



Perfect fit in a 90 cm cabinet



Possibility to freely move the pot everywhere without turn off the initial settings chosen.



Overheat protection: The safety system that automatically turns off the hob in case of overheating of the control unit.



Melting function, suitable for slowly melting delicate foods such as chocolate or butter.



Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids.



Quick selection, with one touch cooking begins at the highest level, then automatically reduces after time. Ideal for dishes that require quick boiling and then continued cooking without constant control (eg beef broth).



Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.



Time elapsed: shows how long the cooking zone has been in use.



Min diameter pot detection of 9 cm.



Automatic Boiling function: a sensor confirms once the boiling point has been reached and then an acoustic alert signals that the ingredients can be added, saving time and energy.



Kinderslot: sommige modellen zijn voorzien van een apparaat om het programma / de cyclus te vergrendelen zodat het niet kan per ongeluk veranderd



Additional maximum power level for a better energy consumption



This function allows you to keep cooked food warm without burner it



Induction: The work of these hobs is based on the principle of electromagnetic induction. The heat is generated directly in the bottom of the pan during its contact with the hob.



Multizone: allows several pans to be used at once, large or small, offering freedom of placement and greater flexibility



All cooking zones can be reduced to the minimum power level, so the hob can be left unattended for a short period without food overcooking or burning. Then just press again this function, the previously set power levels can be reactivated.



Quick Start function: the chosen temperature is reached faster. The heating element works at maximum power until the right temperature is reached.



Simmering function: ideal for long-cooking recipes, preventing food from boiling over or sticking to the pan.



Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time.



Possibility to set the maximum power absorbion of the hob.