

SPD505

Family	Professional dishwasher
Subfamily	Undercounter
Type	Undercounter dishwashers
Crockery	Crockery; Glasses; Cutlery; GN1/1 trays
Basket dimensions	500x500 mm
Control panel	Electronic
Rinse pump	HTR system
Wash pump	Standard
Power connection	400 V 3N~ / 12 A / 7,3 kW / 50 Hz
Product dimensions WxDxH	578x600x814 mm



Target

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs; Hotels; Ristoranti / Catering; Bakeries / Pastry shops; Care facilities ; Catering; Commercial food services; Butcher shops / Delicatessens
------------	---

Aesthetics

Led color	Red	Series	Ecoline
-----------	-----	--------	---------

Technical Features

Trays number	7 x GN1/1	Max. inlet temperature	60°C
Trays washing option	Yes	Max water hardness	5°f - 3°dH
Water consumption per cycle	3,2 l	Inlet pressure	100-1000 kPa
Wash temperature (min-max)	60 °C	Detergent load	1,5 l/h
Rinse temperature (min-max)	85 °C	Rinse load	0,4 l/h
Min. water connection temperature	8°C	Usable load height	340 mm
Minimum water consumption per cycle	3,2 l	Depth with open door	1000 mm

Programs

Programs	3 automatic programs; Self-cleaning programs
Program options	Extra rinse; Clean water cycle
Program table	Electronic Ecoline dishwasher 500
Maximum basket/hour	40
Maximum dishes/hour	720
Maximum glasses/hour	1440

Electrical Connection

Tank heating element power	2000 W	Default connection	7300 W
Boiler heating element power	6100 W	Optional electrical connection	230 V 3~ / 19 A / 7,3 kW / 50 Hz; 230 V 3~ / 19 A / 6,8 kW / 50 Hz; 230 V~ / 15 A / 3,4 kW / 50 Hz; 230 V~ / 17 A / 3.9 kW / 50 Hz; 230 V~ / 20 A / 4,5 kW / 50 Hz; 230 V~ / 22 A / 5,0 kW / 50 Hz; 400 V 3N~ / 12 A / 6,8 kW / 50 Hz
Wash pump power	700 W		

Interface

Display	4 digit	Manual diagnostic	Yes
On/Off button	Yes		

Construction

Tank Construction	Deep drawn Partial double wall	Filter	4-stages filter system
Tank material	Stainless steel AISI 304	Tank capacity	16 l
Back panel	St/steel	Boiler capacity	6 l
Upper washing system	One washing and one split rinse spray arms, stainless steel	Boiler type	Atmosferic boiler
Lower washing system	One washing and one combined rinse spray arms, stainless steel and plastic	Noise	Lpa 54,5 dBA
Tank filter	Plastic	Protection class	IPX4
Door gasket	Only up	Adjustable feet	Yes
Rack guides	Embossed	Drain max. height	600 mm

Accessories Included


Dish basket	1x PB50D01	Water supply hose	Yes - 1,5m
Cutlery basket	1x PHOOS04	Drain hose	Yes - 2m
Flat basket	1x PB50G02		

Equipments

Drain pump	Yes	Option for auto daily switch on	Yes, default OFF
Peristaltic detergent dispenser	Electronic control	Cycle counter	Yes
Peristaltic rinse-aid dispenser	Electronic control	Break tank	Yes
Default chemicals dosing unit of measure	gr/lt	Partial renewal of water in the tank and built-in drain pump	Yes
Rinse boiler Thermostop system	Yes - default	Water supply pipe diameter	DN15 - ½"
Wash tank Thermostop system	Yes	Drain supply pipe diameter	DN20-G 3/4"
Wash pump soft start system	Yes	Detergent (red) hose length	2,2m
Stand-by system	Yes	Rinse aid (blue) hose length	2,2m

Logistic Information

EAN code	8017709327613	Net weight	54,000 kg
Packed product dimensions (WxDxH)	990x660x700 mm	Gross weight (kg)	62,000 kg




R	PANNELLO RETRO LOWER BACK PANEL
Q	MORSETTO EQUIPOTENZIALE EARTH TERMINAL
P	TUBI POMPE PERISTALTICHE PERISTALTIC HOSES
E	CAVO ALIMENTAZIONE ELETTRICA ELECTRICITY SUPPLY CABLE
S	TUBO DI SCARICO DRAIN HOSE
T	ENTRATA CAVO DI ALIMENTAZIONE DOSATORE ESTERNO EXTERNAL DISPENSER POWER CABLE ENTRY POINT
C	TUBO DI CARICO FILLER HOSE

Compatible Accessories



PB50D01

Polypylene basket for 18 plates,
500x500x105 mm



PB50G02

Universal flat bottom polypropylene
basket, 500x500x170 mm



PHOGR5

Glass basket for 500x500 mm
glasswashers



PHOOS01

Polypropylene single basket for
cutlery



PHOOS04

4 compartments polypropylene basket
for cutlery



WB50D01

Wire basket for 18 dishes 250 mm
max. diameter or self service trays,
500x500 mm



WB50G01

Universal wire basket with flat bottom,
500x500x123 mm



WB50G02

Wire basket for 90 mm diameter max
glasses with sloped bottom,
500x500x170 mm



WB50G03

Wire basket for 72 mm diameter glasses
with inclined bottom, 500x500x235 mm



WB50G04

Wire basket for glasses 135 mm
diameter max, with sloped bottom,
500x500x170 mm



WB50PG5

Wire basket for no. 25 plastic glasses
with flat bottom, 500x500x260 mm



WB50T02

Wire basket for 7 trays GN1/1 h 20
mm, 500x500 mm



WH00S01

Wire insert for 12 small dishes



WS5

Underframe for glasswashers and
dishwashers 500, 595x595x490 mm

Benefit (TT)

Interface

Control panel with electronic buttons

The electronic control panel features an intuitive interface with soft-touch buttons, allowing easy selection of one of the three wash programmes: short, medium, or intensive. There are also buttons for power, selection, and cycle start. The display provides real-time monitoring of the tank and boiler temperature, as well as diagnostics, ensuring effortless and immediate control of the main functions.

4-stage filtration system

Deep cleaning and spotless washes with the Patented 4-Stages Filtration System

The innovative Smeg filtration system consists of 4 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd stages, finer particles are captured at this filtration stage; the 3th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Partial double skin

Optimised thermal and acoustic insulation

The double-skin design of the Ecoline features dual insulation on the door, top, and rear panel, while the side panels have a single layer of insulation. This structure optimises energy efficiency by minimising heat loss. Additionally, it provides effective acoustic insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.