

# SPD513S

Family	Professional dishwasher
Subfamily	Undercounter dishwashers
Line	Easyline
Basket dimensions	500x500 mm
Wash pump	Standard

## Accessories Included

Dish basket	1x PB50D01	Water supply hose	Yes - 2m
Cutlery basket	1x PHOOS02	Drain hose	Yes - 2m
Flat basket	1x PB50G02		

## Target

Solutions	Hotels; Restaurants/Pubs; QSR
-----------	----------------------------------

## Programs

Programs	6 automatic programs; 1 fully customizable program; Self-cleaning programs
Program options	Extra rinse; Clean water cycle
Program table	Easyline dishwasher and traywasher 500
Program specifications	Boiler 71°C/Tank 60°C - 1'20"; Boiler 71°C/Tank 60°C - 2'10"; Boiler 85°C/Tank 60°C - 60"; Boiler 85°C/Tank 60°C - 1'10"; Boiler 85°C/Tank 60°C - 3'; Boiler 85°C/Tank 60°C - 4'10"; Boiler 85°C/Tank 60°C - 1'30"
Maximum basket/hour	60
Maximum dishes/hour	1080
Maximum glasses/hour	2160

## Interface

Display	8 digit	Detergent missing alert	Yes
---------	---------	-------------------------	-----

Number of buttons	5	Cycle progress alert	Yes
On/Off button	Yes	End-cycle alert	Yes
Salt alert	Yes	Manual diagnostic	Yes
Rinse aid missing alert	Yes		

## Construction

Tank	Deep drawn	Door gasket	On 3 sides
Construction	Integral double-skin	Rack guides	Embossed
Tank material	Stainless steel AISI 304	Filter	5-stage filter system
Back panel	Galvanized	Tank capacity	11 l
Balanced door	Yes	Boiler capacity	6 l
Upper wash system	One wash and one split rinse spray arms, stainless steel	Protection class	IPX4
Lower wash system	One wash and one split rinse spray arms, stainless steel	Adjustable feet	Yes
Tank filter	Stainless steel	Drain max. height	600 mm

## Technical Features

Trays washing option	Yes	Max. inlet temperature	60°C
Trays number	7 x GN 1/1 (530 x 325 mm)	Max water hardness	54°F - 30°dH
Tank heating element power	2000 W	Inlet pressure	250-1000 kPa (min-max)
Boiler heating element power	6100 W	Detergent load	1,5 l/h
Wash pump power	700 W	Rinse load	0,4 l/h
Default connection	7300 W	Usable load height	400 mm
Water consumption per cycle	3,2 l	Depth with open door	1020 mm
Minimum water consumption per cycle	3,2 l	Product dimensions WxDxH	600x600x822 mm
Warm water connection	5°C		


## Electrical Connection

Plug	Not present	Optional electrical connection	230 V 3~ / 19 A / 7,3 kW / 50 Hz; 230 V 3~ / 19 A / 6,8 kW / 50 Hz; 230 V~ / 15 A / 3,4 kW / 50 Hz; 230 V~ / 17 A / 3.9 kW / 50 Hz; 230 V~ / 20 A / 4,5 kW / 50 Hz; 230 V~ / 22 A / 5,0 kW / 50 Hz; 400 V 3N~ / 12 A / 6,8 kW / 50 Hz
Power connection	400 V 3N~ / 12 A / 7,3 kW / 50 Hz		

## Equipments

Drain pump	Yes	Stand-by system	Yes
------------	-----	-----------------	-----

Peristaltic detergent dispenser	Electronic control	Option for auto daily switch on	Yes, default OFF
Peristaltic rinse-aid dispenser	Electronic control	Cycle counter	Yes
Chemicals level probe	Yes, with optional kit KITSONLIV	Partial renewal of water in the tank and built-in drain pump	Yes
Default chemicals dosing unit of measure	gr/lt	Water supply pipe diameter	DN15 - ½"
Automatic built softener	Yes	Drain supply pipe diameter	DN20-G 3/4"
Rinse boiler Thermostop system	Yes - default	Detergent (red) hose lenght	2,2m
Wash tank Thermostop system	Yes	Rinse aid (blue) hose lenght	2,2m
Wash pump soft start system	Yes		



## Compatible Accessories




### KITDETKCC500

Kit for detergent (1l) and rinse aid (1l) storage for double wall models




### KITSONLIV

Chemical level sensor probe kit for undercounter double wall models and hoodtype models




### PB50D01

Polypropylene basket for 18 plates  
Ø250 mm, dim. (WxDxH) 500x500x105 mm



### PB50G02

Universal flat bottom polypropylene basket, dim. (WxDxH) 500x500x170 mm



### PB50T01

Polypropylene basket for 8 trays GN 1/1  
h 40 mm



### PHOGR5

Glass insert for 500x500 mm basket




### PHOOS01

Polypropylene single basket for cutlery



### PHOOS02

6 compartment polypropylene basket for cutlery



### WB50G01

Universal wire basket with flat bottom,  
dim. (WxDxH) 500x500x123 mm



### WB50G02

Wire basket with sloped bottom for glasses Ø90 mm max, dim. (WxDxH) 500x500x170 mm



### WB50G03

Wire basket with sloped bottom for glasses Ø72 mm max, dim. (WxDxH) 500x500x235 mm



### WB50G04

Wire basket with sloped bottom for glasses Ø135 mm max, dim. (WxDxH) 500x500x165 mm



### WB50PG5

Wire basket with flat bottom for 25 plastic glasses, dim. (WxDxH) 500x500x260 mm



### WB50T02

Wire basket for 7 trays GN1/1 h 20 mm



### WH00S01

Wire insert for 12 small dishes



### WS5

Underframe for glasswashers 500mm

## Symbols glossary

---



SUITABLE FOR GASTRONORM TRAY



5 STAGE FILTER



MAX. USABLE HEIGHT 400mm

## Benefit (TT)

---

### Balanced door

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

### 5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

### Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

### Integrated softener

Effective water treatment for consistently sparkling glasses

The integrated continuous regeneration water softener ensures effective water treatment, enhancing washing performance and preserving the machine's operational lifespan. The resin regeneration process takes place during the wash cycle without interruptions, providing constant control over water hardness. This system prevents limescale buildup, maximises detergent efficiency, and guarantees spotless results on glassware and dishes.

### Integral double-skin

Thermal and acoustic insulation guaranteed

The double-skin design of undercounter dishwashers is engineered to optimise energy efficiency by minimising heat loss and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

### Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

---

## Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.