

SPD525S

Familia	Lavavajillas
Subfamilia	Undercounter dishwashers
Line	Pura
Dimensiones de la cesta	500x500 mm
Rinse pump	Self-Adaptive HTR+
Wash pump	Variable speed AdaptWash



Equipo accesorios incluidos

Cesta de platos	PB50D01	Tubería de suministro de agua	Si - 2m
Cesta de cubiertos	PHOOS02	Tubo de desagüe	Si - 2m
Cesta plana	1x PB50G02		

Distribución

Usuarios potenciales	Hoteles; Restaurantes - Pubs; QSR
-----------------------------	--------------------------------------

Programas

Programs	10 programas personalizables; Programas de autolimpieza
Program options	Aclarado extra; Ciclo de agua limpia
Program table	Pura dishwasher 500
Program visibility	Sí
Máximo cesto / hora	45
Máximo platos / hora	810
Máximo copas / hora	1620

Interface

Pantalla	TFT	Alerta falta de detergente	Sí
Botón ON/OFF	Sí		
Alerta de sal	Sí		

Alerta de falta de abrillantador	Sí	Alerta de progreso del ciclo	Sí
		Alerta de fin de ciclo	Sí

Construcción

Cuba	Produndidad del dibujo	Bomba de desagüe	Sí
Construcción de la cuba	Pared Doble	Filter presence sensor	Sí
Material de la cuba	Acero inoxidable AISI 304	Capacidad de la cuba	11 l
Panel trasero	Galvanizado	Volumen del calderín	6,5 l
Puerta equilibrada	Sí	Ruido	Lpa 56,5 dBA
Upper wash system	Un brazo rociador para lavado y un brazo rociador para aclarado, de acero inoxidable.	Puerto USB	Sí
Lower wash system	Un brazo rociador para lavado y un brazo rociador dividido para aclarado, de acero inoxidable.	Clase de protección	IPX4
Filtro de la cuba	Acero inoxidable	Adjustable feet	Sí
Junta de la puerta	En 3 lados	Profundidad de carga	600 mm
Guías de estante	En relieve		

Características técnicas


Trays washing option	Sí	Minimum water consumption per cycle	1,8 l
Trays number	7 x GN 1/1 (530 x 325 mm)	Entrada de agua	5°C
Tank heating element power	2000 W	Max. inlet temperature	60°C
Boiler heating element power	5700 W	Dureza máxima del agua	54°f - 30°dH
Wash pump power	700 W	Entrada de agua	100-1000 kPa (min-max)
Conexión por defecto	8400 W	Dosificador de detergente peristáltico	Si, manual
Water consumption per cycle	2,5 l	Dosificador de detergente peristáltico	Si, manual
Wash temperature (min-max)	60 °C - 70 °C	Altura útil de carga	400 mm
Rinse temperature (min-max)	65 °C - 87 °C	Profundidad puerta abierta	1020 mm
Cold rinse temperature	24 °C	Product dimensions WxDxH	600x600x822 mm

Conexión eléctrica

Conexión eléctrica	400 V 3N~ / 15 A / 8,4 kW / 50 Hz	Opción de conexión eléctrica	230 V 3~ / 24 A / 8,4 kW / 50 Hz; 230 V~ / 14 A / 3,1 kW / 50 Hz; 230 V~ / 31 A / 7,1 kW / 50 Hz
---------------------------	-----------------------------------	-------------------------------------	--

Equipamiento

Bomba de desagüe	Sí	Option for auto daily switch on	Si, por defecto desactivado
Peristaltic detergent dispenser	Si, control electrónico	Contador de ciclos	Sí
Peristaltic rinse-aid dispenser	Si, control electrónico	Tanque de rotura	Sí
Nivel de productos químicos	Si, opcional KITSONLIV	Renovación parcial del agua en el tanque e incorporación bomba de drenaje	Sí
Descalcificador incorporado	Sí	Diámetro del tubo de entrada de agua	Si - 1,5m
Rinse boiler Thermostop system	Yes - default	Diámetro del tubo de desagüe	Si - 2m
Wash tank Thermostop system	Sí	Dosificador de detergente peristáltico	Si, manual
Wash pump soft start system	Sí	Dosificador de detergente peristáltico	Si, manual
Stand-by system	Sí		



Accesories Compatible

KITDETCCC500




Kit for detergent (1l) and rinse aid (1l) storage for double wall models



KITSONLIV

Chemical level sensor probe kit for undercounter double wall models and hoodtype models

PB50D01




Cesta de polipropileno para 18 platos, 500x500x105 mm



PB50G01

Universal flat bottom polypropylene basket, dim. (WxDxH) 500x500x100 mm

PB50G02



Cesta universal de polipropileno de fondo plano, 500x500x170 mm



PB50T01

Polypropylene basket for 8 trays GN 1/1 h 40 mm

PHOOS01




PHOOS02

WB50D01



Cesta de alambre para 18 platos 250 mm máx. bandejas de diámetro o autoservicio, 500X500mm



WB50G01

Cesta de alambre universal con fondo plano, 500x500x123 mm

WB50G02



Cesta de alambre para vasos de 90 mm de diámetro máximo con fondo inclinado, 500x500x170 mm



WB50G03

Cesta de alambre para vasos de 72 mm de diámetro con fondo inclinado, 500x500x235 mm

WB50G04




Cesta de alambre para vasos de 135 mm de diámetro máximo, con fondo inclinado, 500x500x170 mm



WB50PG5

Wire basket with flat bottom for 25 plastic glasses, dim. (WxDxH) 500x500x260 mm

WB50T02



Cesta de alambre para 7 bandejas GN1/1 h 20 mm, 500x500 mm



WH00S01



WS5

Estructura inferior para lavavasos 500, 595x595x490 mm

Symbols glossary

	THERMODESINFECTION A0=30		THERMODESINFECTION A0=60
	SUITABLE FOR GASTRONORM TRAY		HTR RINSING SYSTEM
	5 STAGE FILTER		MAX. USABLE HEIGHT 400mm
	Professional appliance with Wi-fi connectivity and remote control via Remote SmegConnectPro App.		Electrodoméstico dotado de conexión a la red Wi-Fi

Benefit (TT)

Balanced door

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR+ System

Self-adaptive rinsing system for intelligent water management

The self-Adaptive HTR+ System monitors and adjusts the rinse volume with each wash cycle. The intelligent rinse management ensures the perfect amount of water and heat on the dishes, delivering consistent, reliable results, cycle after cycle.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integrated softener

Effective water treatment for consistently sparkling glasses

The integrated continuous regeneration water softener ensures effective water treatment, enhancing washing performance and preserving the machine's operational lifespan. The resin regeneration process takes place during the wash cycle without interruptions, providing constant control over water hardness. This system prevents limescale buildup, maximises detergent efficiency, and guarantees spotless results on glassware and dishes.

Integral double-skin

Thermal and acoustic insulation guaranteed

The double-skin design of undercounter dishwashers is engineered to optimise energy efficiency by minimising heat loss and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

Mi Lavado Personal

10 programas personalizables para satisfacer todas las necesidades de lavado

Cada modelo de la gama PURA ofrece 10 programas probados, asegurando soluciones listas para cualquier necesidad de lavado. Con la función MyPersonal Wash, se pueden personalizar parámetros como el tiempo, la temperatura, la presión y las opciones de lavado, optimizando los ciclos para vajilla delicada o suciedad resistente. El resultado es un lavado a medida, siempre impecable.

AdaptWash system

Consistently perfect washing pressure for flawless results with every wash

The AdaptWash system offers 3 pressure levels that automatically adjust based on the selected program, ensuring optimal cleaning for every type of load.

Program visibility

Program selection displayed for simplified dishwasher management

Users can select the programs to be displayed, hiding those that are unnecessary or unused. This feature not only helps prevent improper use of the appliance but also represents a significant step towards fully customising the user experience.