

SPG415

Family	Professional dishwasher
Subfamily	Undercounter glasswashers
Line	Easyline
Basket dimensions	400x400 mm
Rinse pump	HTR system
Wash pump	Standard



Accessories Included

Glass basket	1x WB40G02	Water supply hose	Yes - 1,5m
Cutlery basket	1x PHOOS01	Drain hose	Yes - 2m
Flat basket	1x WB40G01		

Target

Solutions	Coffee shops/Wine bars; Restaurants/Pubs
-----------	---

Programs

Programs	6 automatic programs; 1 fully customizable program; Self-cleaning programs; Cold water rinse program
Program options	Extra rinse; Clean water cycle
Program table	Easyline glasswasher 400
Program specifications	Boiler 71°C/Tank 60°C - 1'20"; Boiler 71°C/Tank 60°C - 2'10"; Boiler 85°C/Tank 60°C - 1'10"; Boiler 85°C/Tank 60°C - 2'; Boiler 85°C/Tank 60°C - 3'; Boiler 85°C/Tank 60°C - 4'10"; Boiler 85°C/Tank 60°C - 1'30"
Maximum basket/hour	60
Maximum dishes/hour	480
Maximum glasses/hour	1500

Interface

Display	8 digit	Detergent missing alert	Yes
---------	---------	-------------------------	-----

Number of buttons	5	Cycle progress alert	Yes
On/Off button	Yes	End-cycle alert	Yes
Rinse aid missing alert	Yes	Manual diagnostic	Yes

Construction

Tank	Deep drawn	Rack guides	Embossed
Construction	Integral double-skin	Filter	5-stage filter system
Tank material	Stainless steel AISI 304	Tank capacity	7 l
Back panel	Galvanized	Boiler capacity	4 l
Balanced door	Yes	Noise	Lpa 56 dBA
Upper wash system	One wash and one split rinse spray arms, stainless steel	Protection class	IPX4
Lower wash system	One wash and one split rinse spray arms, stainless steel	Adjustable feet	Yes
Tank filter	Stainless steel	Drain max. height	600 mm
Door gasket	On 3 sides		

Technical Features

Tank heating element power	2000 W	Inlet pressure	100-1000 kPa (min-max)
Boiler heating element power	4300 W	Detergent load	1,5 l/h
Wash pump power	300 W	Rinse load	0,4 l/h
Default connection	5200 W	Usable load height	315 mm
Water consumption per cycle	2,3 l	Depth with open door	930 mm
Minimum water consumption per cycle	2,3 l	Maximum dishes diameter	300 mm
Warm water connection	5°C	Maximum glasses height	300 mm
Max. inlet temperature	60°C	Product dimensions WxDxH	460x600x705 mm
Max water hardness	12°F - 7°dH		


Electrical Connection

Plug	Not present	Optional electrical connection	230 V 3~ / 15 A / 4,6 kW / 50 Hz ; 230 V 3~ / 15 A / 5,2 kW / 50 Hz; 230 V~ / 11 A / 2,5 kW / 50 Hz; 230 V~ / 14 A / 3,1 kW / 50 Hz; 230 V~ / 14 A / 3.2 kW / 50 Hz ; 230 V~ / 17 A / 3.8 kW / 50 Hz
Power connection	400 V 3N~ / 10 A / 5,2 kW /50 Hz		

Equipments

Drain pump	Yes	Option for auto daily switch on	Yes, default OFF
------------	-----	------------------------------------	------------------

Peristaltic detergent dispenser	Electronic control	Cycle counter	Yes
		Break tank	Yes
Peristaltic rinse-aid dispenser	Electronic control	Partial renewal of water in the tank and built-in drain pump	Yes
Chemicals level probe	Yes, with optional kit KITSONLIV	Water supply pipe diameter	DN10 - 3/8"
Rinse boiler Thermostop system	Yes - default	Drain supply pipe diameter	DN20-G 3/4"
Wash tank Thermostop system	Yes	Detergent (red) hose lenght	2,2m
Wash pump soft start system	Yes	Rinse aid (blue) hose lenght	2,2m
Stand-by system	Yes		



Compatible Accessories



KITDETKCC400

Kit for detergent (1l) and rinse aid (1l) storage for double wall models



PHOGR4

Glass insert for 400x400 mm basket



PHOOS02

6 compartment polypropylene basket for cutlery



RB40G01

Universal wire basket with flat bottom, dim. (ØxH) 400x140 mm



WB40G01

Universal wire basket with flat bottom, dim (WxDxH) 400x400x120 mm



WB40G03

Sloped bottom 3 compartments wire basket for glasses Ø120 mm max, dim. (WxDxH) 400x400x168 mm



WH00S01

Wire insert for 12 small dishes



KITSONLIV

Chemical level sensor probe kit for undercounter double wall models and hoodtype models



PHOOS01

Polypropylene single basket for cutlery



RB40A3

Adapter for round basket for all glasswasher models 460 mm wide



WB40D01

Wire basket for 8 dishes Ø315 mm, dim. 400x400 mm



WB40G02

Wire basket with sloped bottom for glasses Ø90 mm max, dim. (WxDxH) 400x400x168 mm



WB40PG4

Wire basket for plastic glasses, dim. (WxDxH) 400x400x210 mm



WS4

Stainless steel underframe for glasswashers, dim. (WxDxH) 495x530x490 mm

Symbols glossary



HTR RINSING SYSTEM



5 STAGE FILTER



Max usable height 315mm

Benefit (TT)

Balanced door

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integral double-skin

Thermal and acoustic insulation guaranteed

The double-skin design of undercounter dishwashers is engineered to optimise energy efficiency by minimising heat loss and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.