

SPG425H

Product Family	Dishwasher
Subfamily	Undercounter
Type	Undercounter glasswashers
Crockery	Crockery; Glasses; Cutlery
Basket dimensions	400x400 mm
Control Panel	Touch screen
Standard drain pump with partial water renewal in the wash tank	Yes
Rinse pump	Self-Adaptive HTR+
Boiler type	Atmospheric Boiler
Wash pump	Standard
SHR system	Yes
Default power supply	400 V 3N~ / 15 A / 6,6 kW / 50 Hz
Dimensions	460x600x760 mm



Target

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs, Hotels, Ristoranti / Catering, Bakeries / Pastry shops, Commercial food services
------------	---

Aesthetics

Led colour	White	Series	Pura
------------	-------	--------	------

Technical Features

Water consumption per cycle	2 l	Water inlet pressure	100-1000 kPa
Wash temperature (min-max)	60 °C - 70 °C	Detergent flow rate	1.5 l/h
Rinse temperature (min-max)	65 °C - 85 °C	Rinse aid flow rate	0.4 l/h
Cold rinse temperature	24 °C	Usable load height	315 mm
Min. water connection temperature	8°C	Depth with door open	930 mm
Minimum water consumption per cycle	1,8 l	Maximum plate diameter	300 mm
Max. inlet temperature	20°C	Maximum glass height	300 mm
Max water hardness	5°f - 3°dH		

Programmes

Programs	10 customizable programs; Self-cleaning programs
Program options	Extra rinse, Clean water cycle
Program table	Pura undercounter 400
Program visibility	Yes
Maximum baskets/hour	60
Maximum plates/hour	480
Maximum glasses/hour	1500

Connectivity

SmegConnect	Yes	PST certificate support	24 months
Connectivity	Wi-Fi	period [UK]	
		UK PSTI support period	2027-12-31
		end date	

Electrical Connection

Tank heating element power	2000 W	Default connection	6600 W
Boiler heating element power	4300 W	Electrical connection options	230 V 3~ / 20 A / 6,6 kW / 50 Hz; 230 V~ / 11 A / 2,45 kW / 50 Hz; 230 V~ / 14 A / 3,2 kW / 50 Hz; 230 V~ / 29 A / 6,6 kW / 50 Hz
Wash pump power	300 W	Plug	No

Interface

Display	TFT	Low detergent alert	Yes
Number of buttons	5	Cycle progress indicator	Yes
On/off indicator	Yes	End of cycle indicator	Yes
Low rinse aid alert	Yes	Manual diagnostics	Yes

Construction

Tank	Deep drawn	Filter	5-stages filter system
Construction	Double wall	Filter presence sensor	Yes
Tank material	Stainless steel AISI 304	Wash tank capacity	7 l
Back panel	Stainless steel	Boiler capacity	4 l
Counter balanced door	Yes	Noise level	Lpa 55 dBA
Upper washing system	One washing and one split rinse spray arms, stainless steel	USB port	Yes
		Protection class	IPX4
		Adjustable feet	Yes
Lower washing system	One washing and one split rinse spray arms, stainless steel	Drain max. height	600 mm

Tank filter	Stainless steel
Door gasket	On 3 sides
Rack guides	Embossed

Accessories Included


Glass basket	WB40G02	Water supply pipe	Yes - 1.5m
Cutlery basket	PHOOS01	Drain pipe	Yes - 2m
Flat basket	WB40G01		

Equipment

Peristaltic detergent dispenser	Yes, electronic control	Option for auto daily switch on	Yes
Peristaltic rinse-aid dispenser	Yes, electronic control	Break tank	Yes
Chemical level probe	Yes, optional KITSONLIV	Water supply pipe diameter	DN10 - 3/8"
Rinse boiler Thermostop system	Yes - default	Drain supply pipe diameter	DN20-G 3/4"
Wash tank Thermostop system	Yes	Detergent (red) hose length	2,2 m
Wash pump soft start system	Yes	Rinse aid (blue) hose length	2,2 m
Stand-by system	Yes		

Logistic Information

EAN code	8017709357009	Net weight (kg)	46,000 kg
Packed product dimensions (WxDxH)	515x710x850 mm	Gross weight (kg)	52,000 kg



Compatible Accessories



KITDETKCC400

Kit for detergent (1l) and rinse storage (1l) for dishwashers 400x400



PB40C02

Universal flat bottom polypropylene double basket, 400x400x125 mm



PHOOS01

Single basket in polypropylene for cutlery



RB40G01

Universal wire basket with flat base 400



WB40G01

Universal wire basket with flat bottom 400x400



WB40G03

Wire basket for 8 glasses, inclined bottom, 4-row 400x400



WH00S01

Wire insert for 12 small dishes



KITSONLIV

Probe level kit



PHOGR4

Glass basket for 400x400 glasswashers



RB40A3

Adapter for round basket



WB40D01

Wire basket for 8 dishes 400x400



WB40G02

Wire basket for 8 glasses, max diameter 90mm, inclined bottom 400x400



WB40PG4

Wire basket for 16 plastic glasses, max. H 180 mm, min.-max. Ø 36-95 mm, dim. (WxDxH) 400x400x210 mm



WS4

Underframe for glasswasher 400mm

Benefit

Balanced door

Effortless opening and closing

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR+ System

Self-adaptive rinsing system for intelligent water management

The self-Adaptive HTR+ System monitors and adjusts the rinse volume with each wash cycle. The intelligent rinse management ensures the perfect amount of water and heat on the dishes, delivering consistent, reliable results, cycle after cycle.

SHR+ System

Steam heat recovery system for energy savings and improved work environment quality

SHR+ System: guaranteed savings and comfort

The SHR+ System eliminates 100% of the steam produced during the rinse phase, improving air quality and reducing humidity in work environments. Additionally, it recovers energy from the condensed steam, ensuring up to 25% energy savings and eliminating the costs associated with an external extraction system.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integral double skin

Thermal and acoustic insulation guaranteed

The double wall is designed to optimise energy efficiency by reducing heat loss and accelerating water heating, resulting in lower energy consumption and faster cycle start-up times. Additionally, it provides effective acoustic insulation, helping to reduce noise and ensuring a quieter, more comfortable working environment for the staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

MyPersonal Wash

10 pre-set washing programmes for a complete and ready-to-use solution.

Each model in the PURA range offers 10 tested programmes, ensuring ready-to-use solutions for any washing requirement. With the MyPersonal Wash function, parameters such as time, temperature, pressure, and washing options can be customised, optimising cycles for delicate dishes or stubborn dirt. The result is a tailored wash, always flawless.

Program visibility

Program selection displayed for simplified dishwasher management

Users can select the programs to be displayed, hiding those that are unnecessary or unused. This feature not only helps prevent improper use of the appliance but also represents a significant step towards fully customising the user experience.