

SPG4250

Family	Professional dishwasher
Subfamily	Undercounter glasswashers
Line	Pura
Basket dimensions	400x400 mm
Rinse pump	Self-Adaptive HTR+
Wash pump	Standard
Integrated osmosis system	Yes



Accessories Included

Glass basket	1x WB40G02	Water supply hose	Yes - 1,5m
Cutlery basket	1x PHOOS01	Drain hose	Yes - 2m
Flat basket	1x WB40G01		

Target

Solutions	Coffee shops/Wine bars; Restaurants/Pubs
-----------	---

Programs

Programs	10 customizable programs; Self-cleaning programs
Program options	Extra rinse; Clean water cycle
Program table	Pura glasswasher 400
Program visibility	Yes
Maximum basket/hour	45
Maximum dishes/hour	360
Maximum glasses/hour	1125

Interface

Display	TFT	Detergent missing alert	Yes
Number of buttons	5	Cycle progress alert	Yes
On/Off button	Yes	End-cycle alert	Yes
Rinse aid missing alert	Yes	Manual diagnostic	Yes

Construction

Tank	Deep drawn	Filter	5-stage filter system
Construction	Integral double-skin	Filter presence sensor	Yes
Tank material	Stainless steel AISI 304	Tank capacity	7 l
Back panel	Galvanized	Boiler capacity	4 l
Balanced door	Yes	Noise	Lpa 56 dBA
Upper wash system	One wash and one split rinse spray arms, stainless steel	USB port	Yes
Lower wash system	One wash and one split rinse spray arms, stainless steel	Protection class	IPX4
Tank filter	Stainless steel	Adjustable feet	Yes
Door gasket	On 3 sides	Drain max. height	600 mm
Rack guides	Embossed		

Technical Features

Tank heating element power	2000 W	Max. inlet temperature	35°C
Boiler heating element power	4300 W	Max water hardness	20°f - 11°dH
Wash pump power	300 W	Inlet pressure	150-1000 kPa (min-max)
Default connection	6600 W	Detergent load	1,5 l/h
Water consumption per cycle	2 l	Rinse load	0,4 l/h
Wash temperature (min-max)	60 °C - 70 °C	Usable load height	315 mm
Rinse temperature (min-max)	65 °C - 85 °C	Depth with open door	930 mm
Cold rinse temperature	24 °C	Maximum dishes diameter	300 mm
Minimum water consumption per cycle	1,8 l	Maximum glasses height	300 mm
Warm water connection	5°C	Product dimensions WxDxH	460x600x825 mm


Electrical Connection

Plug	Not present	Optional electrical connection	230 V 3~ / 20 A / 6,6 kW / 50 Hz; 230 V~ / 11 A / 2,45 kW / 50 Hz; 230 V~ / 14 A / 3,2 kW / 50 Hz; 230 V~ / 29 A / 6,6 kW / 50 Hz
Power connection	400 V 3N~ / 15 A / 6,6 kW / 50 Hz		

Equipments

Drain pump	Yes	Option for auto daily switch on	Yes, default OFF
Peristaltic detergent dispenser	Electronic control		

Peristaltic rinse-aid dispenser	Electronic control	Cycle counter	Yes
Chemicals level probe	Yes, with optional kit KITSONLIV	Break tank	Yes
Rinse boiler Thermostop system	Yes - default	Partial renewal of water in the tank and built-in drain pump	Yes
Wash tank Thermostop system	Yes	Water supply pipe diameter	DN10 - 3/8"
Wash pump soft start system	Yes	Drain supply pipe diameter	DN20-G 3/4"
Stand-by system	Yes	Detergent (red) hose lenght	2,2m
		Rinse aid (blue) hose lenght	2,2m



Compatible Accessories



PB40C02

Universal flat bottom polypropylene double basket, dim. (WxDxH) 400x400x227 mm



PHOGR4

Glass insert for 400x400 mm basket



WB40PG4

Wire basket for plastic glasses, dim. (WxDxH) 400X400X210 mm

Symbols glossary

	HTR RINSING SYSTEM		5 STAGE FILTER
	Max usable height 315mm		Professional appliance with Wi-fi connectivity and remote control via Remote SmegConnectPro App.
	Wi-Fi connectivity		

Benefit (TT)

Balanced door

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR+ System

Self-adaptive rinsing system for intelligent water management

The self-Adaptive HTR+ System monitors and adjusts the rinse volume with each wash cycle. The intelligent rinse management ensures the perfect amount of water and heat on the dishes, delivering consistent, reliable results, cycle after cycle.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integral double-skin

Thermal and acoustic insulation guaranteed

The double-skin design of undercounter dishwashers is engineered to optimise energy efficiency by minimising heat loss and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

MyPersonal Wash

10 pre-set washing programmes for a complete and ready-to-use solution

Each model in the PURA range offers 10 tested programmes, ensuring ready-to-use solutions for any washing requirement. With the MyPersonal Wash function, parameters such as time, temperature, pressure, and washing options can be customised, optimising cycles for delicate dishes or stubborn dirt. The result is a tailored wash, always flawless.

Osmosis system

Glasses always sparkling, without streaks or water spots, straight from the machine

The integrated osmosis system ensures spotless, streak-free glasses, eliminating the need for manual drying. Osmosis water enhances detergent and rinse aid, preventing mineral residue buildup. Housed in a removable drawer, the system simplifies maintenance, allowing the appliance to operate even during extraction.

Program visibility

Program selection displayed for simplified dishwasher management

Users can select the programs to be displayed, hiding those that are unnecessary or unused. This feature not only helps prevent improper use of the appliance but also represents a significant step towards fully customising the user experience.