SPG525L

Type	Undercounter glasswashers
Crockery	Crockery; Glasses; Cutlery
Basket dimensions	500x500 mm
Control Panel	Touch screen
Standard drain pump with partial water renewal in the wash tank	Yes
Rinse pump	Self-Adaptive HTR+
Boiler type	Atmospheric Boiler
Wash pump	Variable speed AdaptWash
Default power supply	400 V 3N~ / 15 A / 8,4 kW / 50 Hz
Dimensions	600x600x722 mm



Target

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs, Hotels, Restaurants / Catering, Bakeries / Pastry shops, Commercial food services

Aesthetics

Led colour	**Series**	Pura

Technical Features

Water consumption per cycle	2,5 l
Wash temperature (min-max)	60 °C - 70 °C
Rinse temperature (min-max)	65 °C - 87 °C
Cold rinse temperature	24 °C
Min. water connection temperature	8°C
Minimum water consumption per cycle	1,8 l
Max. inlet temperature	60°C
Max water hardness	5°f - 3°dH
Water inlet pressure	100-1000 kPa
Detergent flow rate	1.5 l/h
Rinse aid flow rate	0.4 l/h
Usable load height	300 mm
Depth with door open	925 mm
Maximum plate diameter	300 mm
Maximum glass height	300 mm

Programmes

Programs	10 customizable programs; Self-cleaning programs
Program options	Extra rinse, Clean water cycle
Program table	Pura glasswasher 500
Program visibility	Yes
Maximum baskets/hour	45
Maximum plates/hour	810
Maximum glasses/hour	1620

Connectivity

SmegConnect	Yes
Connectivity	Wi-Fi
PST certificate support period [UK]	24 months
UK PSTI support period end date	2027-12-31

Electrical Connection

Tank heating element power	2000 W
Boiler heating element power	5700 W
Wash pump power	700 W
Default connection	8400 W
Electrical connection options	230 V 3~ / 24 A / 8,4 kW / 50 Hz; 230 V~ / 14 A / 3,1 kW / 50 Hz; 230 V~ / 31 A / 7,1 kW / 50 Hz
Plug	No

Interface

Display	TFT Touch 4.3"
On/off indicator	Yes
Low rinse aid alert	Yes
Low detergent alert	Yes
Cycle progress indicator	Yes
End of cycle indicator	Yes
Manual diagnostics	Yes

Construction

Tank	Deep drawn
Construction	Double wall
Tank material	Stainless steel AISI 304
Back panel	Stainless steel
Counter balanced door	Yes
Upper washing system	One washing and one split rinse spray arms, stainless steel
Lower washing system	One washing and one split rinse spray arms, stainless steel
Tank filter	Stainless steel
Door gasket	On 3 sides
Rack guides	Embossed
Filter	5-stages filter system
Wash tank capacity	11 l
Boiler capacity	6,5 l
Noise level	Lpa 54,5 dBA
USB port	Yes
Protection class	IPX4
Adjustable feet	Yes
Drain max. height	600 mm
Power cable length	180 cm

Accessories Included


Flat basket	1x WB50G02	**Drain pipe**	Yes - 2m
Water supply pipe	Yes - 2m		

Equipment

Peristaltic detergent dispenser	Yes, electronic control	**Option for auto daily switch on**	Yes
Peristaltic rinse-aid dispenser	Yes, electronic control	**Cycle counter**	Yes
Chemical level probe	Yes, optional KITSONLIV	**Break tank**	Yes
Rinse boiler Thermostop system	Yes - default	**Water supply pipe diameter**	DN15 - ½"
Wash tank Thermostop system	Yes	**Drain supply pipe diameter**	DN20-G 3/4"
Wash pump soft start system	Yes	**Detergent (red) hose length**	2,2 m
Stand-by system	Yes	**Rinse aid (blue) hose length**	2,2 m

Logistic Information

EAN code	8017709348748	**Net weight (kg)**	60,000 kg
Packed product dimensions (WxDxH)	660x700x890 mm	**Gross weight (kg)**	68,000 kg



1	PANNELLO RETRO - LOWER BACK PANEL
2	MORSETTO EQUIPOTENZIALE - EARTH TERMINAL
3	TUBI POMPE PERISTALTICHE - PERISTALTIC HOSES
4	CAVO ALIMENTAZIONE ELETTRICA - ELECTRICITY SUPPLY CABLE
5	TUBO DI SCARICO - DRAIN HOSE
6	ENTRATA CAVO DI ALIMENTAZIONE DOSATORE ESTERNO - EXTERNAL DISPENSER POWER CABLE ENTRY POINT
7	TUBO DI CARICO - FILLER HOSE

Compatible Accessories




KITDETKCC500

Kit for detergent (1l) and rinse storage (1l) for dishwashers 500x500




KITSONLIV

Probe level kit




PB50D01

Basket made of polypylene for 18 plates 500x500



PB50G01

Universal basket in polypropylene 500x500



PB50G02

Universal basket in polypropylene 500x500



PHOOS01

Single basket in polypropylene for cutlery



WB50D01

Wire basket for 18 dishes and trays 500X500



WB50G01

Universal wire basket with flat bottom 500x500



WB50G02

Wire basket for glasses with inclined bottom 500x500



WB50G03

Wire basket for glasses with inclined bottom 500x500



WB50G04

Wire basket for glasses with inclined bottom 500x500



WB50PG5

Wire basket with flat bottom for 25 plastic glasses, max. H 230 mm, min.-max. Ø 36-95 mm, dim. (WxDxH) 500x500x260 mm



WB50T02

Wire basket for 5 trays 600x500



WH00S01

Wire insert for 12 small dishes



WS5

Underframe for glasswahsers 500mm

Benefit

Balanced door

Effortless opening and closing

Effortless opening and closing
The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.
The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR+ System

Self-adaptive rinsing system for intelligent water management

The self-Adaptive HTR+ System monitors and adjusts the rinse volume with each wash cycle. The intelligent rinse management ensures the perfect amount of water and heat on the dishes, delivering consistent, reliable results, cycle after cycle.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integral double skin

Thermal and acoustic insulation guaranteed

The double wall is designed to optimise energy efficiency by reducing heat loss and accelerating water heating, resulting in lower energy consumption and faster cycle start-up times. Additionally, it provides effective acoustic insulation, helping to reduce noise and ensuring a quieter, more comfortable working environment for the staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

MyPersonal Wash

10 pre-set washing programmes for a complete and ready-to-use solution.

Each model in the PURA range offers 10 tested programmes, ensuring ready-to-use solutions for any washing requirement. With the MyPersonal Wash function, parameters such as time, temperature, pressure, and washing options can be customised, optimising cycles for delicate dishes or stubborn dirt. The result is a tailored wash, always flawless.

AdaptWash system

Consistently perfect washing pressure for flawless results with every wash

The AdaptWash system offers 3 pressure levels that automatically adjust based on the selected program, ensuring optimal cleaning for every type of load.

Program visibility

Program selection displayed for simplified dishwasher management

Users can select the programs to be displayed, hiding those that are unnecessary or unused. This feature not only helps prevent improper use of the appliance but also represents a significant step towards fully customising the user experience.