

SPH515

Family	Professional dishwasher
Subfamily	Hoodtype dishwasher
Basket dimensions	500x500 mm
Panel	Easyline
Filter	5-stages filter system
Rinse pump H.T.R. system	Yes
Dual heating	Yes
Usable load height	470 mm
Power connection	400 V 3N~ / 16 A / 9,7 kW / 50 Hz
Maximum height with open hood	2138 mm
Product dimensions WxDxH	634x750x1523 mm



Target

Solutions	Coffee shops/Wine bars; Hotels; Restaurants/Pubs; Food retail; Catering and Institutions; QSR
-----------	--

Aesthetics

Series	Easyline	Led color	Green
Control panel	electronic		

Functions



Functionality	GN 1/1 trays washing; 5- stage filter; HTR; Door clearance 470mm
---------------	--

Programs

Programs	6 automatic programs; 1 fully programmable program; Self-cleaning programs; Cold water rinse program
Program options	Extra rinse; Clean water cycle
Program specifications	Boiler 85°C/Tank 60°C - 60"; Boiler 71°C/Tank 60°C - 1'20"; Boiler 85°C/Tank 60°C - 1'10"; Boiler 85°C/Tank 60°C - 1'30"; Boiler 71°C/Tank 60°C - 2'10"; Boiler 85°C/Tank 60°C - 2'40"; Boiler 85°C/Tank 60°C - 4'10"
Drain and self cleaning cycle	Yes

Maximum basket/hour	60
Maximum dishes/hour	1080

Interface

Display	8 digit	Cycle progress alert	Yes
On/Off button	Yes	End-cycle alert	Yes
Rinse aid missing alert	Yes	Manual diagnostic	Yes
Detergent missing alert	Yes		

Construction

Tank	Deep drawn	Tank capacity	14 l
Construction	Double wall	Boiler capacity	10 l
Tank material	Stainless steel AISI 304	Noise	Lpa 59,9 dBA
Back panel	Prepainted	Protection class	IPX4
Tank filter	Stainless steel	Adjustable feet	Yes
Washing spray arm	2 in stainless steel	Net weight	122,000 kg
Rinse spray arm	2 in stainless steel	Drain max. height	1000 mm
Hood construction	Double wall		

Technical Features

Tank heating element	2200 W	Warm water connection	8°C
Boiler heating element	9000 W	Max temperature inlet water	60°C
Washing pump	700 W	Max water hardness	12°F - 7°dH
Default connection	9700 W	Inlet pressure	100-1000 kPa
Water cycle consumption	3,2 l		

Electrical Connection

Plug	Not present	Optional electrical connection	230 V 3~ / 28 A / 9,7 kW / 50 Hz; 230 V~ / 16 A / 3,7 kW / 50 Hz (NC); 230 V~ / 29 A / 6,7 kW / 50 Hz
------	-------------	--------------------------------	---


Equipments

Drain pump	Yes	Rinse load	0,4 l/h
Peristaltic detergent doser	Electronic control	Cycle counter	Yes
Peristaltic rinse-aid doser	Electronic control	Break tank	Yes
Chemicals level probe	Yes, with optional kit KITSONLIV	Partial renewal of water in the tank and built-in drain pump	Yes
Default chemicals dosing unit of measure	gr/lt	Trays washing option GN1/1 530x325mm	Yes

Thermostop system	Yes	Water supply pipe diameter	DN15 - ½"
Soft Start system	Yes	Drain supply pipe diameter	DN20-G 3/4"
Stand-by system	Yes	Detergent (red) hose lenght	2,2m
Automatic start	Yes, default OFF	Rinse aid (blue) hose lenght	2,2m
Detergent load	1,5 l/h		

Accessories Included

Dish basket	1x PB50D01	Water supply hose	Yes - 2m
Cutlery basket	1x PHOOS02	Drain hose	Yes - 2m
Flat basket	1x PB50G02		



Not included accessories



WT5700SR

Entry table right side with sink, backsplash (100mm), lower shelf, 700x720x821,5 mm



WT51200SR

Entry table right side with sink, backsplash (100mm), lower shelf, 1200x720x821,5 mm



PHOOS03

8 compartments polypropylene basket for cutlery suggested for Hood Type



WT5700SL

Entry table left side with sink, backsplash (100mm), lower shelf, 700x720x821,5 mm




WT51200SHL

Entry table left side with sink and scraping hole, backsplash (100mm), lower shelf, 1200x720x821,5 mm



PHOOS01

Polypropylene single basket for cutlery




PB50G02

Universal flat bottom polypropylene basket, 500x500x170 mm



WTX51200L

Exit table left side, with backsplash (100mm), with lower shelf, 1200x720x821,5 mm



WB50G01

Universal wire basket with flat bottom, 500x500x123 mm



WTX51200

Exit table for both sides, with lower shelf, 1200x560x821,5 mm

WB50PG5

Wire basket for no. 25 plastic glasses with flat bottom, 500x500x260 mm



KITSONLIV

Probe level kit for double wall models



PHOGR5

Glass basket for 500x500 mm glasswashers



WH00S01

Wire insert for 12 small dishes



WTX5700R

Exit table right side, with back splash (100mm) and lower shelf, 700x720x821,5 mm



WB50T02

Wire basket for 7 trays GN1/1 h 20 mm, 500x500 mm




WT51200SHR

Entry table right side with sink and scraping hole, backsplash (100mm), lower shelf, 1200x720x821,5 mm



WT51200SL

Entry table left side with sink, backsplash (100mm), lower shelf, 1200x720x821,5 mm



PB50D01

Polypylene basket for 18 plates,
500x500x105 mm



WTX51200R

Exit table right side, with backsplash
(100mm), with lower shelf,
1200x720x821,5 mm



WTX5700

Exit table for both sides, with lower
shelf, 700x560x821,5 mm



WB50D01

Wire basket for 18 dishes 250 mm max.
diameter or self service trays, 500X500
mm



WTX5700L

Exit table left side, with back splash
(100mm) and lower shelf,
700x720x821,5 mm



WB50G02

Wire basket for 90 mm diameter max
glasses with sloped bottom,
500x500x170 mm



WB50G04

Wire basket for glasses 135 mm
diameter max, with sloped bottom,
500x500x170 mm



PHOOS02

6 compartments polypropylene
basket for cutlery



WB50G03

Wire basket for 72 mm diameter
glasses with inclined bottom,
500x500x235 mm

Symbols glossary (TT)



SUITABLE FOR GASTRONORM TRAY



HTR RINSING SYSTEM



MAX. USABLE HEIGHT 470mm



5 STAGE FILTER