

SPH615AU

Family	Dishwasher
Subfamily	Hoodtype dishwasher
Type	Hoodtype
Basket dimensions	600x500 e 500x500 mm
Rinse pump	HTR system
Wash pump	Standard
Power connection	400 V 3N~ / 16 A / 9,7 kW / 50 Hz



Distribution

Solutions	Restaurants/Catering; Bakery/Pastry making; Industrial pastry&bakery laboratories; Butcher's shops; Meat processing industry; Schools
-----------	--

Aesthetics

Serie	Easyline	Led color	Green
-------	----------	-----------	-------

Technical Features

Trays washing option	Yes	Max. inlet temperature	60°C
Trays number	7 x GN 1/1 (530 x 325 mm); 6 x EN 1/1 (600 x 400 mm)	Max water hardness	12°f - 7°dH
Water consumption per cycle	3,2 l	Water inlet	100-1000 kPa
Wash temperature (min-max)	58 °C	Detergent load	Yes, manual
Rinse temperature (min-max)	24 °C - 87 °C	Rinse load	Yes, manual
Minimum water consumption per cycle	3,2 l	Usable load height	470 mm
Water inlet	8°C	Product dimensions WxDxH	734x750x1523 mm

Programs

Programs	6 automatic programs; 1 fully programmable program; Self-cleaning programs
Program options	Extra rinse; Clean water cycle
Program table	Easyline hoodtype
Maximum basket/hour	51
Maximum dishes/hour	1122
Maximum glasses/hour	3360

Electrical Connection

Tank heating element power	2200 W	Default connection	9730 W
Boiler heating element power	9000 W	Electrical connection option	230 V~ / 16 A / 3,7 kW / 50 Hz; 230V~ / 26 A / 9,7 kW / 50 Hz ; 230 V~ / 30 A / 6,7 kW / 50 Hz
Wash pump power	700 W		

Interface

Display	8 digit	Cycle progress alert	Yes
On/Off button	Yes	End-cycle alert	Yes
Rinse aid missing alert	Yes	Manual diagnostic	Yes
Detergent missing alert	Yes		

Construction

Tank Construction	Deep drawn Double-skin hood	Hood elevation system	Manual
Tank material	Stainless steel AISI 304	Filter	5-stages filter system
Back panel	St/steel	Tank capacity	22 l
Upper washing system	One washing and one split rinse spray arms, stainless steel	Boiler capacity	10 l
Lower washing system	One washing and one split rinse spray arms, stainless steel	Protection class	IPX4
Tank filter	Stainless steel	Adjustable feet	Yes
		Drain max. height	1000 mm

Accessories Included

Dish basket	PB60D01	Water supply pipe	Yes - 2m
Cutlery basket	PHOOS03	Drain pipe	Yes - 2m
Flat basket	PB60G01		

Equipments

Drain pump	Yes	Option for auto daily switch on	Yes, default OFF
-------------------	-----	--	------------------

Compatible Accessories




KITSONLIV

Probe level kit



PB50G01

Universal basket in polypropylene
500x500



PB50T01

Polypropylene basket for 8 trays GN 1/1
h 40 mm



PB60G01

Universal basket in polypropylene
600x500



PHOOS01

Single basket in polypropylene for
cutlery



PHOOS03

Basket in polypropylene with 6
compartment for cutlery for Capote



WB50G01

Universal wire basket with flat bottom
500x500



WB50G04

Wire basket for glasses with inclined
bottom 500x500




WB60D02

Wire basket for 24 dishes 600X500



PB50D01

Basket made of polypylene for 18
plates 500x500




PB50G02

Universal basket in polypropylene
500x500



PB60D01

Basket in polypropylene for 22 dishes
600x500



PB60T02

Basket for trays GN1/1 600x500



PHOOS02

Basket in polypropylene for cutlery
with 6 compartments




WB50D01

Wire basket for 18 dishes and trays
500X500



WB50G02

Wire basket for glasses with inclined
bottom 500x500



WB60D01

Wire basket for 24 dishes 600X500




WB60G01

Wire basket with flat bottom
600x500

WB60T03

Wire basket for 5 trays 600x500



WH00S01

Wire insert for 12 small dishes



WT51200SHL

Entry table left side 1200mm



WT51200SHR

Entry table right side 1200mm



WT51200SL

Entry table left side 1200mm



WT51200SR

Entry table right side 1200mm



WT5700SL

Entry table left side 700mm



WT5700SR

Entry table right side 700mm



WTX51200

Exit table both sides 1200mm



WTX51200L

Exit table left side 1200mm



WTX51200R

Exit table right side 1200mm



WTX5700

Exit table both sides 700mm



WTX5700L

Exit table left side 700mm



WTX5700R

Exit table right side 700mm



WTX6700F

Tavolo di entrata/uscita 700mm con
aggancio frontale



Symbols glossary



...



...



...



5 STAGE FILTER



MAX. USABLE HEIGHT 470mm

Benefit (TT)

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Double-skin hood

Thermal and acoustic insulation guaranteed

The double-skin design of the hood is engineered to optimise energy efficiency by minimising heat dispersion and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

Hood lift

Unprecedented comfort with the patented lifting system

The new ergonomic handle, combined with the patented lifting system, minimises the effort required to open and close the hood, limiting it to just 2.5 kg. This system ensures an exceptionally smooth and lightweight operation, helping to protect the operator's health and well-being, even during extended use.

Euronorm

Compatibility with EN 600x400 mm trays

The 500x500 traywashers offer great versatility, with the ability to wash up to 6 Euronorm 600x400 mm trays. These features make the products extremely useful for a wide range of activities, such as pizzerias, bakeries, bistros, catering, restaurants, and cafés.