

SPO5L2SL



Família	Fornos
Subfamília	Forno a vapor combinado 5 tabuleiros GN1/1
Tipo de energia	Elétrico
Tipo de forno	Forno Galileo profissional
Fonte de energia	400 V 3N~ / 17 A / 8 kW / 50-60 Hz
Pés reguláveis em altura	Sim
Dimensões do produto (LxPxA)	790x833x645 mm
Profundidade máxima com a porta aberta	1567 mm



Mercado

Indústrias	Hotelaria; Restaurantes; Padarias / Pastelarias; Indústrias Alimentares; Estabelecimentos de Cuidados; Retalho alimentar; Catering e cantinas
-------------------	--

Design

Porta com tiras em aço inox	Sim	Cor dos dígitos no display	Multicolor
Cor Display	Aço Inox/Preto	Painel frontal	Vidro/Aço Inox

Comandos

Nº de programas em memória	512	Função de pausa	Ajustável
Receitas	Sim	Forced cooling	Sim
Temporizador	de 1 min até 23h59 min por passo	Regulação da chaminé	Automático
Função MultiStep	8 + preheating + keep warm	Programas de lavagem	Sim
Início diferido	Sim; Não	HACCP data	Sim
Pré-aquecimento	Sim	Auto diagnóstico	Sim

Opções

Exaustor compatível K510X

Acessórios incluídos

Sonda térmica Sonda térmica de 4 pontos externos

Ligação elétrica

Ficha elétrica Não

ESPECIFICAÇÕES TÉCNICAS

Material do forno	Aço Inox / Vidro / Plástico	Posição de exaustão	Traseira
Dimensões da cavidade (LxPxAl)	670x560x420 mm	Sistema de arrefecimento	Sim
Material da cavidade	Aço inox	Tipo de temporizador	Elétrico
Níveis de tabuleiros	5	Temperaturas	30-270°C
Suporte dos tabuleiros	Aço inox AISI 304	Aviso de final de cozedura	Sim
Kit de adaptação para tabuleiros 600x400 mm	Sim	Interruptor de segurança com porta aberta	Sim
Distância entre tabuleiros	70 mm	Reset de segurança do termostato	Sim
Material da porta	Vidro triplo	Deflector removível	Sim
Abertura da porta	Lateral	Tipo de detergente	Líquido
Tipo de puxador	Rotativo	Interruptor de luz com porta aberta	Sim
Vidro	Abre com dobradiça	Iluminação	1 lâmpada LED
Potência da ventoinha	200 W	Potência das lâmpadas	3.6 W
RPM da ventoinha	Progressão %	Porta USB	Sim
RPM standard da ventoinha	2850 rpm	Nº de entradas de água	1
RPM da ventoinha na velocidade inferior	1425 rpm	Tubo de carga de água	Sim
Injeção de água em cada ventoinha	Sim	Depósito de detergente exterior	Sim
Níveis de humedificação	Automático / Percentual progressivo	Pressão da entrada de água	200-1000 kPa (min-max)
Steam control	5-100% (min-max)	Comprimento do cabo de alimentação	170 cm
Caldeira aberta	Sim	Painel traseiro	Porta galvanizada
Ø de drenagem	1" 1/2 - DN 40 mm	Proteção IPX	IPX4

Dados de logística

Dimensões do produto embalado (LxPxA) 850x950x700 mm

Peso líquido (kg)


90,000 kg

Peso bruto (kg)

110,000 kg

Código EAN

8017709328085



Acessórios Compatíveis



3743

3751


Kit of 4 flat perforated aluminium tray
EN 600×400 mm



3805

Kit of 4 chrome-plated wire grids EN
600×400 mm

3810



CLB45LSE

Flow meter for filter FB45LSE1100




FB45LSE1100

Water treatment filter for Galileo
Professional oven; 7.907 litres
capacity with 10 Kh hardness and
bypass set 1




G11T

Non-stick GN1/1 tray



G11X8P

8 vertical GN1/1 chicken grid



KITDPEC

Galileo professional external detergent
lance kit



KITSTCK55

Conjunction kit between 2 stacked
Galileo ovens (SPO4 or SPO5)



R4EN6040

Galileo Professional oven tray support
kit for 4 EN 600×400 mm trays

T11TH20

GN1/1 non-stick tray, 20 mm height




TB45LSE




TF11XH2

GN 1/1 perforated aluminium tray, 20
mm height














TMF11TH2

GN 1/1 non-sticking microperforated
tray, 20 mm height



Symbols glossary

	Elétrico: a fonte de energia do forno é a eletricidade.		Fan speed adjustable between 50 and 100% of the speed
	Fan forced heating		Core probe baking by temperature difference (Δt)
	Automatic washing		Barbecue: aquecimento seco para grelhados perfeitos.
	Steam generated by injecting water into the fan and evaporation on the heating element		Saturated steam created by boiling in the cavity
	Steam and hot air combined cooking		Sous-vide baixa temperatura
	Humidity and heat controlled proving		

Benefit (TT)

Hinged opening

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.

WashArt System

Efficient washing, optimised consumption, and minimal space usage

The WashArt washing system, equipped with a rotating nozzle, ensures even distribution of water and detergent within the cavity, providing deep cleaning and quick drying. To meet every need, four washing programmes are available: Short, Medium, Long, and Grill, along with a dedicated rinse programme. Thanks to its advanced technology, WashArt optimises efficiency and reduces consumption, while the rotating nozzle, with its compact design, minimises space usage in the cooking chamber.

Fan speed

Precise fan speed modulation for consistently even cooking results

In the Galileo Professional ovens, the fan speed can be adjusted from a minimum of 50% to a maximum of 100%, in 5% increments. This feature allows for precise customisation of the airflow, perfectly adapting it to the specific needs of each preparation. Thanks to this versatility, it is possible to achieve flawless cooking results, ensuring even and accurate heat distribution. Moreover, precisely adjusting the fan speed helps preserve the delicacy of sensitive foods, preventing exposure to excessive heat and creating the ideal conditions to maintain their lightness and internal structure.

Core probe

Multipoint cooking sensor for precise and uniform results

Optimal precision and control thanks to the four temperature measurement points, ensuring an accurate reading at every stage of cooking. The advanced sensor precisely detects the heat at the core of the food, guaranteeing the ideal cooking level for consistently perfect and uniform results.

SteamArt Technology

Open Boiler system to generate steam directly within the cavity, in quick times and at very low temperatures

Thanks to the innovative Open Boiler system, steam is generated directly within the cavity, in very short times and at very low temperatures (starting from 30°C, ideal for supporting the proofing phase). This system is particularly suited for delicate cooking processes that require the use of 100% steam, ensuring even and gentle cooking that preserves the nutritional properties, taste, and texture of the food.

8 cooking stages

Flexibility and precision in every cooking stage

The ability to set multiple cooking phases, in addition to preheating and keeping warm, gives the combi-steam oven exceptional versatility, responding precisely to the diverse needs of every preparation. Each phase of the cooking process can be customised with great accuracy, optimising results whether it's slow cooking at low temperatures or achieving a perfect final browning. Thanks to the advanced control of steam and heat parameters, it is possible to achieve even cooking on every surface, significantly enhancing the quality of the finished product and ensuring flawless results.

System for external detergent tanks

Efficient cleaning operations and optimal resource management

Some oven models are designed to use an external detergent tank and are equipped with dedicated suction hoses. This solution provides greater autonomy, reducing the need for frequent refills, and significantly simplifies the detergent replenishment process. As a result, cleaning operations become more efficient and continuous, without interruptions, ensuring optimal resource management and high hygiene performance.