

STH950X2

Product family

Hood Type	Hood
Design	Integrated (semi) hood
Extraction	Telescopic
Material	Extraction
Type of steel	Stainless steel
EAN code	Brushed
Hood width	8017709346157
Aesthetic	90 cm
Colour	Universale
Serigraphy colour	Silver
Logo	Black
	Silk screen



Controls

Control setting	Slider
-----------------	--------

Program / Functions

No. of speeds

3

Intensive speed



Technical Features



No. of lights

2

No. of filters

4

Anti-grease filters

Aluminium

Vent outlet

150 mm

Minimum distance from GAS hob

650 mm

Minimum distance from ELECTRIC hob

600 mm

Light type

LED

Light outlet

1 W

Light color temperature

4000 K

scale (K)

Free outlet maximum capacity

770 m³/h

Motor power

250 W

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	310	54
Speed 2	470	59
Speed 3	620	63



Intensive speed	740	66
-----------------	-----	----

Accessories Included

Tube reduction Yes

Electrical Connection

Electrical connection rating	252 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	(I) Australia
Frequency (Hz)	50-60 Hz		



Compatible Accessories

KITFC156



Charcoal filters Kit 2 pieces

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.