

STL7272D


Product Family

Dishwashers

Commercial width 60 cm

Commercial height 82 cm


Installation Fully-integrated built-in

Kitchen panel Not supplied

N° baskets 2

Motor Inverter 2.0

EAN code 8017709357047



Programs



| | | | |
|---------------------------|-------------------------------|---------------|-----|
| N. of programmes | 10+1 | Mix | Yes |
| Washing temperatures | 38, 45, 50, 55, 65, 70, 75 °C | Quiet (-2 dB) | Yes |
| Soak | Yes | Intense | Yes |
| Express 27' | Yes | Self clean | Yes |
| Crystal | Yes | Hygiene 99,9% | Yes |
| Full express - 60 minutes | Yes | Delicate | Yes |
| ECO | Yes | | |

Options



| | | | |
|--------------------|----------------|---------------------------|-----|
| Dry Assist+ option | Yes | 1/2 load FlexiZone option | Yes |
| Delay timer option | Up to 24 hours | Special programs option | Yes |

Baskets



| | | | |
|--------------------------|--------------------------------------|---------------------------------------|------------------|
| Basket colour | Grey | Lower Basket | With fixed racks |
| Basket components colour | Grey | Lower basket with anti-drip inserts | Yes |
| Handle | In plastic on upper and lower basket | Largest loadable dish in lower basket | 30,0 cm |


| | | | |
|--|--------------------------|--------------------------------|-----------|
| Upper Basket | With central fixed racks | Colour Inner Components | Sage Leaf |
| Height adjustment of the upper basket | On three levels (5 cm) | Cutlery basket | Yes |
| Largest loadable dish in upper basket | 25,0 cm | | |

Technical Features



| | | | |
|--------------------------------|---|--|---|
| Width (mm) | 598 mm | Water supply | Single; cold/hot water max. 60°C - energysave with hot water up to 35% |
| Depth (mm) | 545 mm | | 100°fH;58°dH |
| Display type | LED display (3 digit) | Max water hardness | Natural condenser drying, with Dry Assist + automatic door opening system at the end of the cycle |
| Product Height (mm) | 818 mm | Drying system | |
| Controls | Electronic | | |
| Display | Delayed start, Programme time indicator | | |
| Programme graphics | Symbols | Steam protection | In plastic |
| On/off indicator | Yes | Tub material | Stainless steel |
| Salt light indicator | Light | Filter | Stainless steel |
| Rinse aid indicator | Light | Concealed heating element | Yes |
| End of cycle indicator | Acoustic signal | Hinges | Self balancing, Sliding, FLEXIFIT |
| Auto switch-off | Yes | Min. and max. frontal panel weight | 2,5 - 11 kg |
| Washing system | Orbital | Min. and max plinth height | 50 - 215 mm |
| Third spray arm | Single | Adjustable feet | 7 cm, from 820 to 890 mm |
| Water softener | With electronic setting | Back cover | Yes |
| Flood protection system | Total Acquastop | Depth of dishwasher with open door (mm) | 1168 mm |
| | | Back feet adjustable from front | Yes |
| | | Top cover | In plastic |

Performance / Energy Label - Reg. 2019




| | | | |
|--|-------------|---|------------------|
| Energy Efficiency Class | D | Programme duration | 4:10 h:min |
| Energy consumption [per 100 cycles, based on the eco programme] | 84 kWh | Airborne acoustical noise emissions | 47 dB(A) re 1 pW |
| Rated capacity (ps) | 13 | Airborne acoustical noise emission class | C |
| Water consumption [per cycle] | 12,0 litres | Energy efficiency Index (EEI) | 49,9 |

Electrical Connection

| | | | |
|------------------------|--------|---------------------------|--------------|
| Connected power | 1800 W | Type of connection | Single-phase |
|------------------------|--------|---------------------------|--------------|

| | | | |
|-----------------------|-----------|----------------------------------|--------------|
| Current | 10 A | Power supply cable length | 140 cm |
| Voltage | 220-240 V | Plug | |
| Frequency (Hz) | 50 Hz | | (F;E) Schuko |



Compatible Accessories

**KIT82CN****KIT82CX****KIT82SPRAN****KIT82SPRMW****KIT82SPRX****KITPL60B**

Toekick Kit in White colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

**KITPL60X**

Toekick Kit in Stainless Steel with adjustable height and deepness. Can be fitted over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

**KITFLEXI**

Kit for 60cm dishwashers with FlexiFit hinges for door panel weight >11 kg (max 15 kg 82 cm and 13,5 kg 86 cm)

**KITPL60N**

Toekick Kit in Black colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

**KITPLV2**

Kit extension for dishwasher and washing machine: lenght mt. 2

Symbols glossary

| | | | |
|--|---|---|--|
|  | To improve the drying of dishes without leaving stains. |  | Energy efficiency class D |
|  | 82 cm high |  | Delay Timer: Option to postpone the start of the desired programme by up to 24 hours in order to programme the dishwasher to run at the desired time. |
|  | The Dry Assist + option, in addition to saving energy, ensures perfect drying of the dishes by opening the door automatically at the end of the washing cycle. |  | The FlexiFit hinges allow the kitchen panel to slide over the dishwasher door, allowing a minimum kitchen plinth height of 5 cm. |
|  | FlexiZone: The 1/2 load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed. |  | The work aimed at continuous improvement has allowed the creation of the second generation of the Inverter motor 2.0, characterised by greater efficiency and durability over time, which allows very high performance and a lower energy consumption and noise level. |
|  | Noise Level: Excellent insulation and special devices keep noise to a minimum. |  | Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash. |
|  | Crystals: The Crystals programme is dedicated to delicate dishes such as glasses and china. |  | Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled. |
|  | Eco: Eco, this economic wash programme uses a low amount of water and energy in order to provide the most environmentally friendly cleaning option. |  | Quick wash cycle for normally soiled mixed loads such as dishes and pans, even with dried-on residues. Dishes are washed and dried in 60 minutes. |
|  | Mix: The Mix programme is suitable for mixed crockery and everyday pots and pans, without any particular incrustation. |  | Dishwasher cleaning cycle. The cycle should be started with the machine empty, without dishes. It is recommended to run the program every 2-3 months, using special dishwasher detergents. |
|  | SILENT: Wash cycle suitable for normally soiled dishes, even with dried-on residues. Ensures maximum noise reduction and is therefore ideal if you wish to run it during the night. |  | Allows you to enable additional programs when selected together with any wash cycle. |
|  | Soak programme: The soak programme provides a rinse to prevent dirt from drying. |  | Express 27': The Express 27' programme is a quick wash cycle, at low temperatures, for lightly soiled dishes. |
|  | HYGIENE 99.9% High-temperature washing programme. The 75° rinse guarantees the removal of 99.9% of germs and bacteria. |  | Ultraclean: The Ultraclean option performs a final rinse at a high temperature of 70°C eliminating virtually all bacteria. |



13 place settings: Number of place settings.



Total AcquaStop: In addition to the partial AcquaStop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.



System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher.