

# STP364S



Product Family Width Commercial height Installation Kitchen panel N° baskets Motor EAN code Dishwashers 60 cm 82 cm Fully-integrated built-in Not supplied 3, FlexiDuo Inverter 8017709182410



### Programmes

ECO 🚳 🏅 💭	70		
No. of programmes	5+4 quick programmes	Ultra Rapid	Yes
Washing temperatures	45, 50, 55, 65, 70 °C	Mix Express	Yes
Soak	Yes	Auto 60	Yes
Glass	Yes	Universal	Yes
ECO	Yes	Intensive 70°	Yes
Ultraclean	Yes		

### Options



Energy saving option EnerSave Delay timer option

1/2 load FlexiZone option (varied distribution) Yes

Up to 24 hours, with automatic soak Yes

Options for tabs	Yes
FlexiTabs	
Professional option	Yes

### Baskets



Basket colour Basket components colour Stainless Steel Grey Largest loadable dish in 18,0 cm upper basket Lower Basket With comp

With completely foldable racks and glass holder



#### Handle

**Upper Basket** 

Height adjustment of the upper basket Upper basket with EasyGlide System In plastic on upper and lower basket With foldable central racks and glass holder On three levels

Yes

er lowerb Colour Compo

Lower basket with anti-<br/>drip insertsYesLargest loadable dish in<br/>lower basket30,0 cmColour Inner<br/>ComponentsBlue anti drop inserts, Grey<br/>handles, Grey pastic plate<br/>for regulation second<br/>basket on three levels, Grey<br/>Flexiduo, Green OrbitalCutlery basket13 place settings sliding

### **Technical Features**

Width (mm)	598 mm	Water supply	Single; cold/hot water max.
Depth (mm)	545 mm		60°C - energysave with hot
Display type	Display type 3 digit	Max water hardness	water up to 35% 100°fH;58°dH
Product Height (mm) 818 mm			
Controls	Electronic	Drying system	Natural condenser drying, with EnerSave automatic
Display	time indicator, Time to end		door opening system at the end of the cycle
	indication	Steam protection	In plastic
	Programme graphicsSymbolsOn/off indicatorYesSalt light indicatorLightRinse aid indicatorLightEnd of cycle indicatorAcoustic signalWashing systemOrbital	Tank material Filter Concealed heating element	Stainless steel
			Stainless steel
-			Yes
Washing system		Hinges	Self balancing with variable hinges
Third spray arm	Single	Min. and max. frontal	2 - 9 kg
Water softener	With electronic setting	panel weight	
Turbidity sensor Aquatest	•	Min. and max plinth height	100 - 228 mm
Flood protection system	Total Acquastop	Adjustable feet	7cm, from 820 to 890 mm
		Insulation level	Тор
		Back cover	Yes
		Depth of dishwasher with open door (mm)	1146
		Back feet adjustable	Yes

from front Top cover

### Performance / Energy Label



Energy Efficiency ClassE(Washing cycle)92 KWhEnergy consumption92 KWh[per 100 cycles, basedon the eco programme]Rated capacity (ps)14

Airborne acoustical45 dB(A) re 1 pWnoise emissions(spinning phase)Airborne acousticalCnoise emission classEnergy efficiency IndexEnergy efficiency Index54,1(EEI) (Washing cycle)54,1

In plastic



Water consumption [per 10,5 litres cycle]

### **Electrical Connection**

Connected power	
Current	
Voltage	

5450 W 32 A 220-240 V



Frequency (Hz) Type of connection Power supply cable length 50 Hz Single-phase 200 cm



### **Compatible Accessories**



#### KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks

#### KITPL60N



Toekick Kit in Black colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

#### KITPLV2



Kit extension for dishwasher and washing machine: length mt. 2



#### KITPL60B

Toekick Kit in White colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

#### KITPL60X



Toekick Kit in Stainless Steel with adjustable height and deepness. Can be fitted over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



## Symbols glossary

AQUATEST	Aquatest measures the clarity of the water during an auto program, and automatically ensures the minimum consumption of water and energy.	Ň	Anti-drip: Some models of dishwashers are equipped with special polymer nozzles anti-drip, that improve the process of drying.
	A++: Energy efficiency class A++ helps to save up to 20% energy compared to class A. Maximum performance with minimum consumption is guaranteed.	E	Energy efficiency class E
82 cm	COMM_HEIGHT_82_72dpi	$\widehat{\mathbb{Y}}$	Delay Timer: The delay timer can postpone the start of the program by up to 24 hours.
	EasyGlide: Convenient EasyGlide system for easy unloading of the appliance that allows reaching maximum flexibility of load of the machine.	8	Fingerprint proof stainless steel: Fingerprint proof stainless steel keeps stainless steel looking as good as new.
	FlexiDuo: The FlexiDuo 3rd cutlery basket allows you to arrange cutlery or small cups, ladles, or bulky utensils however you like: it consists of two separate and moveable modules.	0	Flexitabs: Flexitabs adjusts the wash cycle to give the best possible results regardless of the type of detergent used.
3	FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.		Inverter technology: The evolution of Smeg's driers towards more intelligent and environmentally sustainable models has led to the choice of using Inverter technology with heat pumps, which reduces significantly energy consumption.
45 dB	Noise Level: Excellent insulation and special devices keep noise to a minimum.	CORDITAL ORBITAL SYSTEM	Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash.
Auto 80	Auto 60°: Program Auto 60 ° is designed for heavily soiled mixed dishes.	ECO 50°	Eco: Eco, this economic wash programme uses a low amount of water and energy in order to provide the most environmentally friendly cleaning option.
灬	Soak programme: The soak programme provides a rinse to prevent dirt from drying.	۵.	Ultra Rapid: The program is specifically for Ultra Fast wash very quickly (16 min.). Pots and pans very dirty, even with dried residues.
70°	Ultraclean: The Ultraclean option performs a final rinse at a high temperature of 70°c eliminating virtually all bacteria.	©.	UniversaleProf: The Universal program is suitable for washing normally soiled tableware, even with little residue dried.
ſ	Professional: Option Professional enables to convert household appliances into semiprofessional ones due to the programs which significantly reduce washing time to obtain an astonishing 16 minutes cycle.	1 <b>Ö</b> ll	The symbols show the number of plate settings of the dishwasher.



 $\approx$ 

Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary. 000 10,5lt

System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher.



### Benefit

#### FlexiDuo

For added convenience, the flexible third basket—FlexiDuo—adapts to accommodate various types of dishes, giving you extra space and better organisation with every load

The third FlexiDuo basket consists of two separate sections that can be handled independently of each other, stacked and/or removed, offering loading flexibility for every need. Depending on the arrangement, it allows cups, tall glasses, bulky utensils and pots and pans to be placed in the upper basket.

#### Orbital Wash System

The Orbital Wash System ensures even water distribution, delivering deep cleaning while keeping noise levels low, thanks to its dual rotating spray arms

Orbital washing system, which, thanks to its double arm, its 7 water exit points and thanks to overlapping and simultaneous rotations and 40 rotations per minute, allows ample coverage of the tank area, thus guaranteeing optimal results in any basket-loading configuration.