

STU1822



Product Family

Commercial height	82 cm
Installation	Fully-integrated built-in
Kitchen panel	Not supplied
Nº baskets	2
Motor	Inverter
EAN code	8017709344177
UPC Code	812895026429



Programs



N. of programmes	6	Super	Yes
Washing temperatures	45, 50, 55, 65 °F	Regular	Yes
Delicate	Yes	Intensive 65°	Yes
Auto	Yes	Rinse	Yes

Options



Hi-Temp	Yes	Delay timer option	Up to 24 hours
Extra Fast	Yes	Extra dry option	Yes
Sanitize	Si	1/2 load FlexiZone option	Yes
Silent	Si		

Baskets

Basket colour	Grey	Height adjustment of the upper basket	On two levels (5cm)
Basket components colour	Grey	Lower Basket	With 2 foldable racks
Handle	In plastic on upper and lower basket	Colour Inner Components	Grey
Upper Basket	With 2 foldable racks	Cutlery basket	Yes


Technical Features



Width (mm)	17 5/8 "	End of cycle indicator	On display, with acoustic signal
Depth (mm)	21 5/8 "		
Display type	LED display (3 digit)	Washing system	Standard
Product Height (mm)	32 5/16 "	Turbidity sensor	Yes
Controls	Electronic	Aquatest	
Display	Delayed start, Programme time indicator	Drying system	Natural condenser drying
Programme graphics	Written in EN	Tub material	Stainless steel
On/off indicator	Yes	Filter	Stainless steel
Rinse aid indicator	Light	Concealed heating element	Yes
		Adjustable feet	5cm, from 820 to 870 mm
		Back feet adjustable from front	Yes

Electrical Connection

Connected power	1400 W	Type of connection	Single-phase
Current	12 A	Power supply cable length	116 "
Voltage	120 V		
Frequency (Hz)	60 Hz	Plug	(B) NEMA 5-15P



Compatible Accessories

KITPL60B



Toekick Kit in White colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

KITPL60X



Toekick Kit in Stainless Steel with adjustable height and deepness. Can be fitted over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

KITPL60N



Toekick Kit in Black colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

KITPLV2



Kit extension for dishwasher and washing machine: lenght mt. 2

Symbols glossary



The Aquatest sensor is an electronic sensor that measures the degree of water transparency at the end of the initial soaking phase. Based on the values measured, the sensor sets the most suitable programme, thus obtaining the best washing results with the minimum amount of water.



Delay Timer: Option to postpone the start of the desired programme by up to 24 hours in order to programme the dishwasher to run at the desired time.



Smeg's evolution towards more intelligent and eco-friendly models has led to the choice of Inverter technology, which significantly reduces consumption.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



PRG_RINSE_72dpi



EXTRA DRY This option adds a hot rinse cycle that ensures improved drying.



82 cm high



FlexiZone: The $\frac{1}{2}$ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



PRG_STRONG_72dpi



The Regular programme is for dishes with regular dirt, even with dried-on residues.