

STU1822



Product family	Dishwashers
Commercial height	82 cm
Installation	Fully-Integrated
Kitchen panel	Not supplied
N° baskets	2
Motor	Inverter
EAN code	8017709344177
UPC Code	812895026429



Programs



Number of programs	6	Super	Yes
Washing temperatures	45, 50, 55, 65 °F	Regular	Yes
Delicates	Yes	Intensive 150°F	Yes
Auto	Yes	Rinse	Yes

Options



Hi-Temp	Yes	Delay start	Up to 24 hours
Extra Fast	Yes	Extra-dry option	Yes
Sanitize	Si	FlexiZone half-load option	Yes
Silent	Si		

Baskets

Basket color	Gray	Upper basket height adjustment	On two levels (5cm)
Basket components finish	Gray	Lower basket	With 2 foldable racks
Handle	In plastic on upper and lower basket	Colour Inner Components	Gray
Upper basket	With 2 foldable racks	Cutlery basket	Yes

Technical Features




Width	17 5/8 "
Depth	21 5/8 "
Display type	LED display (3 digits)
Height	32 5/16 "
Controls	Electronic
Display	Delay start, Program progress indicator
Program symbols	Writings in English
On/off indicator	Yes
Rinse aid indicator	Light
End-of-cycle indicator	On display, with acoustic signal

Washing system	Standard
Turbidity sensor Aquatest	Yes
Drying system	Natural condensation drying
Filter	Stainless steel
Concealed heating element	Yes
Adjustable feet	2", from 32 1/4" to 34 1/4"
Back feet adjustable from front	Yes
Energy Star	

Electrical Connection

Connected power	1400 W
Current	12 A
Voltage	120 V
Frequency	60 Hz

Connection type	Single-phase
Power Cord Length	116 "
Plug	(B) NEMA 5-15P



Compatible Accessories

KIT18SPRX



KITPL60N

Toekick Kit in Black colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

KITPLV2



Kit extension for dishwasher and washing machine: lenght mt. 2



KITPL60B













Toekick Kit in White colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



KITPL60X

Toekick Kit in Stainless Steel with adjustable height and deepness. Can be fitted over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

Symbols glossary

	Aquatest measures the clarity of the water during an auto program, and automatically ensures the minimum consumption of water and energy.		COMM_HEIGHT_82_72dpi
	Delay Timer: The delay timer can postpone the start of the program by up to 24 hours.		FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.
	Inverter technology: The evolution of Smeg's driers towards more intelligent and environmentally sustainable models has led to the choice of using Inverter technology with heat pumps, which reduces significantly energy consumption.		Noise Level: Excellent insulation and special devices keep noise to a minimum.
	Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.		Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.
	PRG_RINSE_72dpi		PRG_STRONG_72dpi
	EXTRA DRY This option adds a hot rinse cycle that ensures improved drying.		The Regular programme is for dishes with regular dirt, even with dried-on residues.