

# STU2FABBL2


**Product Family**
**Commercial height**
**Installation**
**Nº baskets**
**Motor**
**EAN code**
**Dishwashers**
**82 cm**
**Under counter built-in**
**3, FlexiDuo**
**Single phase**
**8017709303594**


## Programs



<b>N. of programmes</b>	10	<b>Delicate</b>	Yes
<b>Washing temperatures</b>	38, 45, 50, 55, 65, 70, 75 °F	<b>Auto</b>	Yes
<b>Soak</b>	Yes	<b>Crystal &amp; China</b>	Yes
<b>Express 27'</b>	Yes	<b>Eco express</b>	Yes
<b>Mix</b>	Yes	<b>Express 60'</b>	Yes
<b>Sterilise</b>	Yes	<b>Pots &amp; Pans</b>	Yes

## Options



<b>Dry Assist option</b>	Yes	<b>Professional option</b>
<b>Delay timer option</b>	Up to 9 hours	<b>Intensive wash zone option</b>
<b>1/2 load FlexiZone option</b>	Yes	<b>Special programs option</b> Yes

## Baskets



<b>Basket components colour</b>	Grey	<b>Largest loadable dish in upper basket</b>
<b>Upper Basket</b>	With 1 foldable rack	<b>Lower Basket</b> With 2 foldable racks
<b>Glass holder</b>	Yes	<b>Largest loadable dish in lower basket</b> 30,0 inches
<b>Height adjustment of the upper basket</b>	On three levels (5 cm)	<b>Cutlery basket</b> Yes

Sliding Guides Extra Yes  
Glide


## Technical Features




<b>Width (mm)</b>	23 9/16 "	<b>Turbidity sensor</b>	Yes
<b>Depth (mm)</b>	21 7/16 "	<b>Aquatest</b>	
<b>Display type</b>	LED display (1 digit)	<b>Flood protection system</b>	Total Acquastop
<b>Product Height (mm)</b>	32 3/16 "	<b>Max water hardness</b>	100°fH;58°dH
<b>Display</b>	Delayed start	<b>Drying system</b>	Natural condenser drying, with Dry Assist automatic door opening system at the end of the cycle
<b>On/off indicator</b>	Yes	<b>Tub material</b>	Stainless steel
<b>Salt light indicator</b>	Light	<b>Filter</b>	Stainless steel
<b>Rinse aid indicator</b>	Light	<b>Concealed heating element</b>	Yes
<b>End of cycle indicator</b>	Acoustic signal	<b>Hinges</b>	Self balancing with fixed hinges
<b>Washing system</b>	Planetarium	<b>Min. and max plinth height</b>	98 - 168 mm
<b>Third spray arm</b>	Single	<b>Adjustable feet</b>	7cm, from 820 to 890 mm
<b>Water softener</b>	With electronic setting	<b>Additional gaskets</b>	Yes
		<b>Back cover</b>	Yes

## Electrical Connection

<b>Connected power</b>	1800 W	<b>Type of connection</b>	Single-phase
<b>Current</b>	13 A	<b>Power supply cable length</b>	140 "
<b>Voltage</b>	115 V	<b>Plug</b>	(A) USA e Messico
<b>Frequency (Hz)</b>	60 Hz		



## Compatible Accessories



### KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks



### KITPL60FABB

Toekick Kit in White colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



### KITPL60FABX

Toekick Kit in Stainless Steel with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



### KITPL60FABN

Toekick Kit in Black colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



### KITLV2

Kit extension for dishwasher and washing machine: lenght mt. 2

---

## Alternative products

---



**STU2FABCR2**

Colour: Cream



**STU2FABRD2**

Colour: Red



**STU2FABWH2**

Colour: White

## Symbols glossary



The Aquatest sensor is an electronic sensor that measures the degree of water transparency at the end of the initial soaking phase. Based on the values measured, the sensor sets the most suitable programme, thus obtaining the best washing results with the minimum amount of water.



Delay Timer: Option to postpone the start of the desired programme by up to 24 hours in order to programme the dishwasher to run at the desired time.



FlexiDuo: The FlexiDuo 3rd cutlery basket allows you to arrange cutlery or small cups, ladles, or bulky utensils however you like: it consists of two separate and moveable modules.



The ExtraGlide guides system makes the second basket run even smoother and softer. It facilitates movement even when fully loaded, and thanks to the increased excursion, facilitates the insertion of dishes into the basket.



The Planetarium washing system, with high rotations per minute, guarantees complete coverage of the tank, thanks to the simultaneous rotation of base and sprayers, and excellent washing results.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



Soak programme: The soak programme provides a rinse to prevent dirt from drying.



13 place settings: Number of place settings.



Allows you to enable additional programs when selected together with any wash cycle.



82 cm high



The Dry Assist option ensures optimal drying of the dishes by automatically opening the door at the end of the wash cycle. Reducing the rinse temperat



FlexiZone: The  $\frac{1}{2}$  load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



Mix: The Mix programme is suitable for mixed crockery and everyday pots and pans, without any particular incrustation.



Express 27': The Express 27' programme is a quick wash cycle, at low temperatures, for lightly soiled dishes.



Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.



STERYL 75°: Intensive wash cycle ideal for plates, pots, pans, cutting boards, feeding bottles.