STU2FABBL2



Product Family	Dishwashers
Commercial height	ADA Compliant
Installation	Under counter built-in
N° baskets	3, FlexiDuo
Motor	Single phase
EAN code	8017709303594

Programs

N. of programmes	10	**Delicate**	Yes
Washing temperatures	38, 45, 50, 55, 65, 70, 75 °F	**Auto**	Yes
Soak	Yes	**Crystal & China**	Yes
Express 27'	Yes	**Eco express**	Yes
Mix	Yes	**Express 60'**	Yes
Sterilise	Yes	**Pots & Pans**	Yes

Options

Dry Assist option	Yes	**Professional option**	
Delay timer option	Up to 9 hours	**Intensive wash zone option**	
1/2 load FlexiZone option	Yes	**Special programs option**	Yes

Baskets

Basket components colour	Grey	**Largest loadable dish in upper basket**	23,5 inches
Upper Basket	With 1 foldable rack	**Lower Basket**	With 2 foldable racks
Glass holder	Yes	**Largest loadable dish in lower basket**	30,0 inches
Height adjustment of the upper basket	On three levels (5 cm)	**Cutlery basket**	Yes

Sliding Guides Extra Glide	Yes


Technical Features




Width (mm)	23 9/16 "
Depth (mm)	21 7/16 "
Display type	LED display (1 digit)
Product Height (mm)	32 3/16 "
Display	Delayed start
On/off indicator	Yes
Salt light indicator	Light
Rinse aid indicator	Light
End of cycle indicator	Acoustic signal
Washing system	Planetarium
Third spray arm	Single
Water softener	With electronic setting
Turbidity sensor Aquatest	Yes
Flood protection system	Total Acquastop
Max water hardness	100°fH;58°dH
Drying system	Natural condenser drying, with Dry Assist automatic door opening system at the end of the cycle
Steam protection	Metallic sheet
Tub material	Stainless steel
Filter	Stainless steel
Concealed heating element	Yes
Hinges	Self balancing with fixed hinges
Min. and max plinth height	98 - 168 mm
Adjustable feet	7cm, from 820 to 890 mm
Additional gaskets	Yes
Back cover	Yes
Energy Star	Yes

Electrical Connection

Connected power	1800 W
Current	13 A
Voltage	115 V
Frequency (Hz)	60 Hz
Type of connection	Single-phase
Power supply cable length	140 "
Plug	(A) USA e Messico


600
598
584
630
min. 575
min. 820
720
818 - 888
120 - 190
50
0 - 78

Compatible Accessories



KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks



KITPL60FABN

Toekick Kit in Black colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPLV2

Kit extension for dishwasher and washing machine: lenght mt. 2

KITPL60FABB

Toekick Kit in White colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPL60FABX

Toekick Kit in Stainless Steel with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.

Alternative products



STU2FABCR2

Colour: Cream



STU2FABRD2

Colour: Red



STU2FABWH2

Colour: White

Symbols glossary



The Aquatest sensor is an electronic sensor that measures the degree of water transparency at the end of the initial soaking phase. ased on the values measured, the sensor sets the most suitable programme, thus obtaining the best washing results with the minimum amount of water.



The Dry Assist option ensures optimal drying of the dishes by automatically opening the door at the end of the wash cycle. Reducing the rinse temperat



FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



Mix: The Mix programme is suitable for mixed crockery and everyday pots and pans, without any particular incrustation.



Soak programme: The soak programme provides a rinse to prevent dirt from drying.



13 place settings: Number of place settings.



STERYL 75°: Intensive wash cycle ideal for plates, pots, pans, cutting boards, feeding bottles.



Delay Timer: Option to postpone the start of the desired programme by up to 24 hours in order to programme the dishwasher to run at the desired time.



FlexiDuo: The FlexiDuo 3rd cutlery basket allows you to arrange cutlery or small cups, ladles, or bulky utensils however you like: it consists of two separate and moveable modules.



The ExtraGlide guides system makes the second basket run even smoother and softer. It facilitates movement even when fully loaded, and thanks to the increased excursion, facilitates the insertion of dishes into the basket.



The Planetarium washing system, with high rotations per minute, guarantees complete coverage of the tank, thanks to the simultaneous rotation of base and sprayers, and excellent washing results.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



Allows you to enable additional programs when selected together with any wash cycle.



Express 27': The Express 27' programme is a quick wash cycle, at low temperatures, for lightly soiled dishes.



Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.