

STU2FABBL2



Product Family
Commercial height
Installation
N° baskets
Motor
EAN code

Dishwashers
82 cm
Under counter built-in
3, FlexiDuo
Single phase
8017709303594



Programs



N. of programmes 10
Washing temperatures 38, 45, 50, 55, 65, 70, 75 °F
Soak Yes
Express 27' Yes
Mix Yes
Sterilise Yes

Delicate Yes
Auto Yes
Crystal & China Yes
Eco express Yes
Express 60' Yes
Pots & Pans Yes

Options



Dry Assist option Yes
Delay timer option Up to 9 hours
1/2 load FlexiZone option Yes

Professional option
Intensive wash zone option
Special programs option Yes

Baskets



Basket components colour Grey
Upper Basket With 1 foldable rack
Glass holder Yes
Height adjustment of the upper basket On three levels (5 cm)

Largest loadable dish in upper basket 23,5 inches
Lower Basket With 2 foldable racks
Largest loadable dish in lower basket 30,0 inches
Cutlery basket Yes

Sliding Guides Extra Glide Yes


Technical Features



Width (mm)	23 9/16 "	Turbidity sensor	Yes
Depth (mm)	21 7/16 "	Aquatest	
Display type	LED display (1 digit)	Flood protection system	Total Acquastop
Product Height (mm)	32 3/16 "	Max water hardness	100°FH;58°dH
Display	Delayed start	Drying system	Natural condenser drying, with Dry Assist automatic door opening system at the end of the cycle
On/off indicator	Yes		
Salt light indicator	Light	Tub material	Stainless steel
Rinse aid indicator	Light	Filter	Stainless steel
End of cycle indicator	Acoustic signal	Concealed heating element	Yes
Washing system	Planetarium	Hinges	Self balancing with fixed hinges
Third spray arm	Single	Min. and max plinth height	98 - 168 mm
Water softener	With electronic setting	Adjustable feet	7cm, from 820 to 890 mm
		Additional gaskets	Yes
		Back cover	Yes

Electrical Connection

Connected power	1800 W	Type of connection	Single-phase
Current	13 A	Power supply cable length	140 "
Voltage	115 V	Plug	(A) USA e Messico
Frequency (Hz)	60 Hz		



Compatible Accessories



KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks



KITPL60FABN

Toekick Kit in Black colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPLV2

Kit extension for dishwasher and washing machine: lenght mt. 2



KITPL60FABB

Toekick Kit in White colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPL60FABX

Toekick Kit in Stainless Steel with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.

Alternative products



STU2FABCR2
Colour: Cream





















STU2FABWH2
Colour: White



STU2FABRD2
Colour: Red

Symbols glossary

	The Aquatest sensor is an electronic sensor that measures the degree of water transparency at the end of the initial soaking phase. Based on the values measured, the sensor sets the most suitable programme, thus obtaining the best washing results with the minimum amount of water.		82 cm high
	Delay Timer: Option to postpone the start of the desired programme by up to 24 hours in order to programme the dishwasher to run at the desired time.		The Dry Assist option ensures optimal drying of the dishes by automatically opening the door at the end of the wash cycle. Reducing the rinse temperature.
	FlexiDuo: The FlexiDuo 3rd cutlery basket allows you to arrange cutlery or small cups, ladles, or bulky utensils however you like: it consists of two separate and moveable modules.		FlexiZone: The 1/2 load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.
	The ExtraGlide guides system makes the second basket run even smoother and softer. It facilitates movement even when fully loaded, and thanks to the increased excursion, facilitates the insertion of dishes into the basket.		Noise Level: Excellent insulation and special devices keep noise to a minimum.
	The Planetary washing system, with high rotations per minute, guarantees complete coverage of the tank, thanks to the simultaneous rotation of base and sprayers, and excellent washing results.		Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.
	Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.		Mix: The Mix programme is suitable for mixed crockery and everyday pots and pans, without any particular incrustation.
	Allows you to enable additional programs when selected together with any wash cycle. After having selected the required wash cycle, press the button (	Soak programme: The soak programme provides a rinse to prevent dirt from drying.
	Express 27': The Express 27' programme is a quick wash cycle, at low temperatures, for lightly soiled dishes.		STERYL 75°: Intensive wash cycle ideal for plates, pots, pans, cutting boards, feeding bottles.
	13 place settings: Number of place settings.		Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.