

# SWT264D

Professional dishwasher Family

Subfamily Dishwasher with thermal disinfection

Washer-disinfectors Type Crockery Crockery; Glasses; Cutlery

Wash pump Standard

Power connection 400 V 3N~ / 12 A / 7 kW / 50 Hz

Product dimensions (WxDxH) 600x600x850 mm



# **Target**

Care facilities **Industries** 

# **Aesthetics**

Led color Orange

## **Technical Features**

Wash pump flow 400 L / min Rinse load 0,4 l/h Min. water connection 5°C Depth with open door 1200 mm temperature 240 mm

Max dish diameter 60°C Max. inlet temperature upper basket

Max water hardness 65°f - 36°dH Max dish height lower 290 mm

basket **Detergent load** 1,5 l/h

# **Programs**

**Programs** 7 automatic programs

Thermodisinfection dishwasher Program table

Preferred program setting Yes **Repeat Function** Yes Regeneration and complete drain cycle Yes 93°C Rinse temperature (max) 34 min

Maximum wash cycle duration with thermal

disinfection

Grade of lethality of thermal disinfection (AI)  $AI = 6.000 (93^{\circ} C / 5') - AI = 12.000 (93^{\circ} C / 10')$ 



Maximum wash cycle duration 8 min Maximum place settings capacity 12 Maximum place settings capacity/hour 90

### **Electrical Connection**

Tank heating element

power

400 W Wash pump power

**Default connection** 

6400 W

6800 W

Optional electrical

connection

230 V 3~ / 19 A / 7 kW / 50 Hz; 220 V~ / 12 A / 2,8 kW /

50 Hz; 230 V~ / 16 A / 3,5

kW / 50 Hz

Plug Not present

## Interface

4 digit Display On/Off button Yes Salt alert Yes Rinse aid missing alert Yes

Detergent missing alert Yes Cycle progress alert Yes End-cycle alert Yes Manual diagnostic Yes

## Construction

Tank Deep drawn

Tank material Stainless steel AISI 304

Back panel Galvanized

Upper wash system One wash and one single

rinse spray arms, stainless

steel

Lower wash system One wash and one single

rinse spray arms, stainless

steel

**Balanced** door Yes

Tank filter Stainless steel Door gasket On 3 sides

Rack guides **Embossed** 

Filter 3-stage filter system

Condensatore Yes

Noise LpA<70 dB(A)

Automatic opening door Yes Adjustable feet Yes

Drain max. height 1000 mm

## Accessories included

Water supply hose Yes - 2 m Drain hose Yes - 2m

# **Equipments**



Drain pump

Peristaltic detergent

dispenser

Peristaltic rinse-aid

dispenser

Chemicals level probe Yes, with optional kit

KSL260

Electronic control

Electronic control

Yes

Cycle counter

Break tank

Door lock

Detergent (red) hose

lenght

Rinse aid (blue) hose

lenght

2,2 m

Yes


Yes

Yes

2,2 m



Automatic built softener Yes Wash pump soft start Yes system





# **Compatible Accessories**

#### AS4060

Kit Aquastop



#### B6040L

Stainless steel closed underframe with push opening, dim. (WxDxH) 600x530x430 mm

#### **KSL260**

Probe level kit for detergent and rinse



Adaptor for PB50D01 and PB50G02 basket



#### **KSP**

Stainless steel kit steam protector



#### LB16SWT

Stainless steel basket for 16 bottles



#### PB50D01

Polypropylene basket for 18 plates Ø250 mm max, dim.(WxDxH) 500x500x105 mm



#### PHOOS02

6 compartment polypropylene basket for cutlery



#### **STNBIN**

Stainless steel front closing plinth



#### T6040

Stainless steel frame stand, dim. 600x530x400 mm



### TOP60I

Copper cover kit when removing built-in panel



# Symbols glossary



Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.



THERMODESINFECTION A0=60



HTR RINSING SYSTEM



THERMO DISINFECTION



## Benefit (TT)

#### Door lock

Maximum safety during the thermodisinfection cycle

The door lock system prevents opening during the thermodisinfection cycle, ensuring the process runs smoothly and safely, avoiding any accidental interruptions that could compromise the effectiveness of the treatment and preventing the risk of contamination.

#### Repeat cycle

The Repeat function reduces consumption by reusing the water from the final rinse

The Repeat function allows the clean water from the final rinse to be reused for the next wash cycle. This feature not only reduces water consumption but also enhances process efficiency, shortening wash times without compromising hygiene or cleaning quality.

#### Integrated softener

Effective water treatment for consistently sparkling glasses

The integrated continuous regeneration water softener ensures effective water treatment, enhancing washing performance and preserving the machine's operational lifespan. The resin regeneration process takes place during the wash cycle without interruptions, providing constant control over water hardness. This system prevents limescale buildup, maximises detergent efficiency, and guarantees spotless results on glassware and dishes.

## Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

#### SWT

Designed to ensure the highest standards of hygiene and cleanliness

These appliances are designed to ensure high standards of hygiene and cleanliness. The thermodisinfection programmes with a 93°C rinse achieve A0 levels of up to 12000, which cannot be reached by traditional professional dishwashers.

#### Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

The tank, featuring rounded corners and integrated basket guides, is designed to prevent dirt build-up and make cleaning the machine quick and easy. The moulded base also helps direct any residue towards the filter, ensuring high levels of hygiene and consistently thorough cleaning.