

UD516D

Familia	Lavavajillas
Tipología	Undercounter traywasher
Dimensiones de la cesta	500x500 mm
Panel de control	Línea Fácil 2016
Rinse pump	HTR system
Conexión eléctrica	400 V 3N~ / 12 A / 6,73 kW / 50 Hz
Product dimensions (WxDxH)	600x675x822 mm



Distribución

Industries	Bakeries / Pastry shops; Food Industries; Comercio minorista de alimentos; Otra industria alimentaria; QSR
-------------------	--

Estética

Color Led	Verde	Serie	Easyline
------------------	-------	--------------	----------

Características técnicas

Water consumption per cycle	3,2 l	Dosificador de detergente peristáltico	Si, manual
Entrada de agua	5°C	Dosificador de detergente peristáltico	Si, manual
Max. inlet temperature	60°C	Altura útil de carga	400 mm
Dureza máxima del agua	12°F - 7°dH	Profundidad puerta abierta	1020 mm
Entrada de agua	Frío 15°C		

Programas

Programs	6 programas automáticos; 1 programa completamente personalizable; Programas de autolimpieza
Program options	Aclarado extra; Ciclo de agua limpia
Máximo cesto / hora	51
Máximo platos / hora	720

Conexión eléctrica

Tank heating element power	2000 W	Conexión por defecto	6730 W
Boiler heating element power	6000 W	Opción de conexión eléctrica	230 V 3~ / 19 A / 6,7 kW / 50 Hz; 230 V~ / 12 A / 2,7 kW / 50 Hz; 230 V~ / 16 A / 3,7 kW / 50 Hz; 230 V~ / 21 A / 4,7 kW / 50 Hz
Wash pump power	730 W		

Interface

Pantalla	8 dígitos	Alerta de progreso del ciclo	Sí
Botón ON/OFF	Sí	Alerta de fin de ciclo	Sí
Alerta de falta de abrillantador	Sí	Diagnostico manual	Sí
Alerta falta de detergente	Sí		

Construcción

Cuba	Profundidad del dibujo	Junta de la puerta	En 3 lados
Construcción de la cuba	Pared Doble	Guías de estante	En relieve
Material de la cuba	Acero inoxidable AISI 304	Bomba de desagüe	Sí
Panel trasero	Galvanizado	Capacidad de la cuba	11 l
Puerta equilibrada	Sí	Volumen del calderín	6.5 l
Upper wash system	Un brazo rociador para lavado y un brazo rociador para aclarado, de acero inoxidable.	Clase de protección	IPX4
Lower wash system	Un brazo rociador para lavado y un brazo rociador dividido para aclarado, de acero inoxidable.	Adjustable feet	Sí
Filtro de la cuba	Acero inoxidable	Profundidad de carga	600 mm

Equipo accesorios incluidos

Cesta de platos	PB50D01	Cesta para bandejas	WB50T03
Cesta de cubiertos	PHOOS02	Tubería de suministro de agua	Si - 2m
Cesta plana	1x PB50G02	Tubo de desagüe	Si - 2m
Rejillas	1 x KIT-WG500		


Equipamiento

Bomba de desagüe	Sí	Option for auto daily switch on	Si, por defecto desactivado
Peristaltic detergent dispenser	Si, control electrónico	Contador de ciclos	Sí
		Tanque de rotura	Sí

Peristaltic rinse-aid dispenser	Si, control electrónico	Renovación parcial del agua en el tanque e incorporación bomba de drenaje	Sí
Nivel de productos químicos	Si, opcional KITSONLIV	Diámetro del tubo de entrada de agua	Si - 1,5m
Dosificación de productos químicos	gr/lt	Diámetro del tubo de desagüe	Si - 2m
Rinse boiler Thermostop system	Yes - default	Dosificador de detergente peristáltico	Si, manual
Wash pump soft start system	Sí	Dosificador de detergente peristáltico	Si, manual
Stand-by system	Sí		

Datos logísticos

Código EAN	8017709260477	Peso neto	66.000 kg
Packed product dimensions (WxDxH)	990x660x700 mm	Peso bruto (kg)	74.000 kg




Accesorios Compatible




KITDETKCC500

Kit for detergent (1l) and rinse aid (1l) storage for double wall models



KIT-WG500

Support grid for tray washer, dim. (WxD) 500x500 mm



PB50G02

Cesta universal de polipropileno de fondo plano, 500x500x170 mm



PHOOS02



WB50T02

Cesta de alambre para 7 bandejas GN1/1 h 20 mm, 500x500 mm




WH00S01



KITSONLIV

Probe level kit



PB50D01

Cesta de polipropileno para 18 platos, 500x500x105 mm



PHOOS01



WB50PG5

Wire basket with flat bottom for 25 plastic glasses, dim. (WxDxH) 500x500x260 mm



WB50T03

Wire basket for 6 trays GN1/1 h 60 mm and EN 600x400 mm, 64 mm row spacing, dim. (WxDxH) 500x500x206



WS5

Estructura inferior para lavavasos 500, 595x595x490 mm

Symbols glossary



SUITABLE FOR EURONORM TRAY



SUITABLE FOR GASTRONORM
TRAY



HTR RINSING SYSTEM



MAX. USABLE HEIGHT 400mm



5 STAGE FILTER

Benefit (TT)

Balanced door

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant rinsing temperature according to the program setting. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

Cuba moldeada

Rendimiento de lavado superior y mayor comodidad de limpieza gracias a fondos de cuba y guías de cestas moldeados.

Los lavavajillas Smeg están diseñados con cuba moldeada y guías para las cestas. La ausencia de bordes afilados garantiza un flujo de lavado optimizado, asegurando higiene y un rendimiento de limpieza impecable. Además, este diseño innovador simplifica la limpieza del aparato, reduciendo la necesidad de intervenciones de mantenimiento.

Integral double-skin

Thermal and acoustic insulation guaranteed

The double-skin design of undercounter dishwashers is engineered to optimise energy efficiency by minimising heat loss and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.