

UD516DS

Familia	Lavavajillas
Subfamilia	Undercounter traywasher
Dimensiones de la cesta	500x500 mm
Rinse pump	HTR system
Wash pump	Standard
Conexión eléctrica	400 V 3N~ / 12 A / 6,73 kW / 50 Hz



Distribución

Usuarios potenciales	Panaderías - Pastelerías; Industria de panadería congelada; Comercio minorista de alimentos; Otra industria alimentaria; QSR
-----------------------------	---

Estética

Serie	Easyline	Color Led	Verde
--------------	----------	------------------	-------

Características técnicas

Trays washing option	Sí	Dosificador de detergente peristáltico	Si, manual
Water consumption per cycle	3,2 l	Dosificador de detergente peristáltico	Si, manual
Entrada de agua	5°C	Altura útil de carga	400 mm
Max. inlet temperature	60°C	Profundidad puerta abierta	1020 mm
Dureza máxima del agua	54°f - 30°dH	Product dimensions WxDxH	600x675x822 mm
Entrada de agua	Frío 15°C		

Programas

Programs	6 programas automáticos; 1 programa completamente personalizable; Programas de autolimpieza
-----------------	---

Program options	Aclarado extra; Ciclo de agua limpia
Máximo cesto / hora	51
Máximo platos / hora	720

Conexión eléctrica

Tank heating element power	2000 W	Conexión por defecto	6730 W
Boiler heating element power	4500 W	Opción de conexión eléctrica	230 V 3~/19 A / 6,7 kW / 50 Hz; 230 V~/12 A / 2,7 kW / 50 Hz; 230 V~/16 A / 3,7 kW / 50 Hz; 230 V~/21 A / 4,7 kW / 50 Hz
Wash pump power	730 W		

Interface

Pantalla	8 dígitos	Alerta falta de detergente	Sí
Botón ON/OFF	Sí	Alerta de progreso del ciclo	Sí
Alerta de sal	Sí	Alerta de fin de ciclo	Sí
Alerta de falta de abrillantador	Sí	Diagnóstico manual	Sí

Construcción

Cuba	Produndidad del dibujo	Guías de estante	En relieve
Construcción de la cuba	Pared Doble	Hood elevation system	Manual
Material de la cuba	Acero inoxidable AISI 304	Bomba de desagüe	Sí
Panel trasero	Galvanizado	Capacidad de la cuba	11 l
Puerta equilibrada	Sí	Volumen del calderín	6.5 l
Upper wash system	Un brazo rociador para lavado y un brazo rociador para aclarado, de acero inoxidable.	Clase de protección	IPX4
Lower wash system	Un brazo rociador para lavado y un brazo rociador dividido para aclarado, de acero inoxidable.	Adjustable feet	Sí
Filtro de la cuba	Acero inoxidable	Profundidad de carga	600 mm
Junta de la puerta	En 3 lados		

Equipo accesorios incluidos


Cesta de platos	PB50D01	Rejillas	1 x KIT-WG500
Cesta de cubiertos	PHOOS02	Tubería de suministro de agua	Si - 2m
Cesta plana	1x PB50G02	Tubo de desagüe	Si - 2m

Equipamiento

Bomba de desagüe	Sí	Stand-by system	Sí
Peristaltic detergent dispenser	Si, control electrónico	Option for auto daily switch on	Si, por defecto desactivado
Peristaltic rinse-aid dispenser	Si, control electrónico	Contador de ciclos	Sí
Nivel de productos químicos	Si, opcional KITSONLIV	Tanque de rotura	Sí
Dosificación de productos químicos	gr/lit	Renovación parcial del agua en el tanque e incorporación bomba de drenaje	Sí
Descalcificador incorporado	Sí	Diámetro del tubo de entrada de agua	Si - 1,5m
Rinse boiler Thermostop system	Yes - default	Diámetro del tubo de desagüe	Si - 2m
Wash tank Thermostop system	Sí	Dosificador de detergente peristáltico	Si, manual
Wash pump soft start system	Sí	Dosificador de detergente peristáltico	Si, manual

Datos logísticos

Ancho del producto empaquetado	660 mm	Dimensiones del producto embalado	990X660X700
Profundidad producto embalado	700 mm	Peso neto	69.000 kg
Altura del producto embalado	990 mm	Peso bruto (kg)	77.000



Accesories Compatible

KITDETCCC500



Kit for detergent (1l) and rinse aid (1l)
storage for double wall models

KITSONLIV



Probe level kit


KIT-WG500

Trays holder for trays washer



PB50D01

Cesta de polipropileno para 18 platos,
500x500x105 mm



PB50G02

Cesta universal de polipropileno de
fondo plano, 500x500x170 mm



PHOOS01




PHOOS02



WB50PG5

Wire basket with flat bottom for 25
plastic glasses, dim. (WxDxH)
500x500x260 mm



WB50T02

Cesta de alambre para 7 bandejas
GN1/1 h 20 mm, 500x500 mm



WB50T03

Wire basket for 6 trays GN1/1 h 60
mm and EN 600x400 mm



WH00S01



WS5

Estructura inferior para lavavasos
500, 595x595x490 mm

Symbols glossary

 EN SUITABLE FOR EURONORM TRAY

 GN1/1 SUITABLE FOR GASTRONORM TRAY

 HTR RINSING SYSTEM

 5 STAGE FILTER

 MAX. USABLE HEIGHT 400mm

Benefit (TT)

Balanced door

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integrated softener

Effective water treatment for consistently sparkling glasses

The integrated continuous regeneration water softener ensures effective water treatment, enhancing washing performance and preserving the machine's operational lifespan. The resin regeneration process takes place during the wash cycle without interruptions, providing constant control over water hardness. This system prevents limescale buildup, maximises detergent efficiency, and guarantees spotless results on glassware and dishes.

Integral double-skin

Thermal and acoustic insulation guaranteed

The double-skin design of undercounter dishwashers is engineered to optimise energy efficiency by minimising heat loss and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

Hood lift

Unprecedented comfort with the patented lifting system

The new ergonomic handle, combined with the patented lifting system, minimises the effort required to open and close the hood, limiting it to just 2.5 kg. This system ensures an exceptionally smooth and lightweight operation, helping to protect the operator's health and well-being, even during extended use.