

# **UG401DM**

**Family** Subfamily

**Basket dimensions** 

**Panel** 

Filter Usable load height

Power connection

Depth with open door

Product dimensions WxDxH

Professional dishwasher Undercounter Glasswasher

400x400 mm

**Ecoline** 

4-stages filter system

309 mm

230 V~ / 13 A / 3,0 kW / 50 Hz

882 mm

440x530x670 mm



# **Target**

**Solutions** 

Coffee shops/Wine bars

## **Aesthetics**

Series

**Ecoline** 

Control panel

electronic

## **Functions**





**Functionality** 

4-stages filter; Door clearance 309mm

# **Programs**

**Programs** 

**Program options** 

**Program specifications** 

Drain and self cleaning cycle Maximum basket/hour

3 automatic programs; Self-cleaning programs

Extra rinse; Clean water cycle

Boiler 85°C/Tank 60°C - 1'30"; Boiler 85°C/Tank 60°C -

2'30"; Boiler 85°C/Tank 60°C - 4'

Yes

40

## Interface

Display

4 digit

On/Off button

Yes



Number of buttons 5 Manual diagnostic Yes

Construction

TankWith printed baseDoor gasketOnly upConstructionPartial double wallRack guidesEmbossed

Tank material Stainless steel AISI 304 Tank capacity 7 I

Back panel Galvanized 4.5 I **Boiler** capacity Double wall **Protection class** IPX4 Door Plastic Tank filter Adjustable feet Yes 2 in stainless steel Washing spray arm Net weight 35.300 kg

Rinse spray arm Plastic Drain max. height 600 mm

**Technical Features** 

Tank heating element 2000 W Warm water connection 8°C

Boiler heating element 2700 W Max temperature inlet 60°C

Boiler heating element 2700 W Max temperature inlet 60°C Washing pump 290 W water

Default connection 3000 W Max water hardness 12°f - 7°dH

Water cycle 3 | Inlet pressure 2,5-6 bar / 250-600 kPa consumption

**Electrical Connection** 

Plug (F;E) Schuko

**Equipments** 

Drain pumpYesRinse load0,4 l/hPeristaltic detergentElectronic controlCycle counterYesdoserPartial represent the foundation of the property of the property

doser Partial renewal of water Yes

Peristaltic rinse-aid Flectronic control in the tank and built-in

Peristaltic rinse-aid Electronic control in the tank and built-in doser drain pump

Deafult chemicals gr/lt Water supply pipe DN15 - ½"

dosing unit of measure diameter

Thermostop system Yes Drain supply pipe DN20-G 3/4"

Soft Start system

Yes

Drain supply pipe

DN20-G 3/4"

diameter


Automatic start Yes, default OFF Detergent (red) hose 2,2m

Detergent load 1,5 l/h lenght
Rinse aid (blue) hose 2,2m lenght

Accessories Included

Cutlery basket1x PHOOS01Water supply hoseYes - 1,5mFlat basket2x PB40G01Drain hoseYes - 2m





R	Pannello retro	Lower back panel
Q	Morsetto equipotenziale	Earth terminal
С	Tubo di carico	Filler hose
S	Tubo di scarico	Drain hose
Р	Tubi pompe peristaltiche	Peristaltic hoses
Е	Cavo alimentazione elettrica	Electricity supply cable



## Not included accessories




#### **RB40G01**

Universal wire basket with flat bottom, Ø 400 mm, h 140 mm



### RB40A3

Adapter for round basket for single wall models and 460 mm glasswashers



# PHOOS01

Polypropylene single basket for cutlery



#### WB40G01

Universal wire basket with flat bottom, 400x400x120 mm



### WB40G02

Sloped bottom 4 compartments wire basket for max 90 mm diameter glasses, 400x400x168 mm



Kit of 2 wire round baskets and adaptor for Ecoline



Wire basket for plastic glasses with flat bottom, 400X400X210 mm



## WS4

Underframe for glasswasher 400, 495x530x490 mm

### WB40G03

Sloped bottom 3 compartments wire basket for max 120 mm diameter glasses, 400x400x168 mm



### PHOOGR4

Glass basket for 400x400 glasswashers



### WB40D01

Wire basket for 16 dishes max diameter 315 mm, 400x400 mm



#### PHOOS02

6 compartments polypropylene basket for cutlery



# Symbols glossary (TT)



4 STAND FILTER



MAX.USABLE HEIGHT 309mm