

UG415D

Familia	Lavavajillas
Subfamilia	Undercounter glasswashers
Dimensiones de la cesta	400x400 mm
Rinse pump	HTR system



Equipo accesorios incluidos

Cesta para copas	WB40G02	Tubería de suministro de agua	Si - 1,5m
Cesta de cubiertos	PHOOS01	Tubo de desagüe	Si - 2m
Cesta plana	WB40G01		

Distribución

Usuarios potenciales	Cafeterías - Vinotecas; Restaurantes - Pubs
----------------------	--

Programas

Programas	4- 71°C / 60°C - 1' 20"; 13- 71°C / 60°C - 2' 10"; 18- 85°C / 60°C - 1' 10"; 7- 85°C / 60°C - 2'; 9- 85°C / 60°C - 3'; 17- 85°C / 60°C - 4' 10"; 5- 85°C / 60°C - 1' 30"
Máximo cesto / hora	72
Máximo platos / hora	576
Máximo copas / hora	960

Interface

Pantalla	TFT	Alerta falta de detergente	Sí
Número de botones	5	Alerta de progreso del ciclo	Sí
Botón ON/OFF	Sí	Alerta de fin de ciclo	Sí
Alerta de falta de abrillantador	Sí	Diagnostico manual	Sí

Construcción

Cuba	Profundidad del dibujo	Guías de estante	En relieve
Construcción de la cuba	Pared Doble	Bomba de desagüe	Sí
Material de la cuba	Acero inoxidable AISI 304	Capacidad de la cuba	7 l
Panel trasero	Galvanizado	Volumen del calderín	4 l
Puerta equilibrada	Sí	Ruido	Lpa 56 dBA
Filtro de la cuba	Acero inoxidable	Clase de protección	IPX4
Junta de la puerta	En 3 lados	Profundidad de carga	600 mm

Características técnicas

Tank heating element power	2000 W	Dosificador de detergente peristáltico	Si, manual
Boiler heating element power	4500 W	Dosificador de detergente peristáltico	Si, manual
Washing pump power	290 W	Altura útil de carga	300 mm
Conexión por defecto	4800 W	Profundidad puerta abierta	850 mm
Entrada de agua	Frío 15°C	Diámetro máximo de platos	300 mm
Temperatura máxima de entrada de agua	60°C	Altura máxima de copas	300 mm
Dureza máxima del agua	12°f - 7°dH	Product dimensions WxDxH	460x600x705 mm

Conexión eléctrica

Conexión eléctrica	400 V 3N~ / 8 A / 4,8 kW / 50 Hz	Opción de conexión eléctrica	230 V 3~ / 13 A / 4,8 kW / 50 Hz; 230 V~ / 8 A / 1,8 kW / 50 Hz; 220 V~ / 11 A / 2,4 kW / 60 Hz; 230 V~ / 15 A / 3,3 kW / 50 Hz; 230 V~ / 21 A / 4,8 kW / 50 Hz
---------------------------	----------------------------------	-------------------------------------	---

Equipamiento

Dosificador de detergente peristáltico	Si, control electrónico	Contador de ciclos	Sí
Dosificador de detergente peristáltico	Si, control electrónico	Tanque de rotura	Sí
Nivel de productos químicos	Si, opcional KITSONLIV	Renovación parcial del agua en el tanque e incorporación bomba de drenaje	Sí
Boiler thermostop	Yes - default	Diámetro del tubo de entrada de agua	Si - 1,5m
Arranque suave	Sí	Diámetro del tubo de desagüe	Si - 2m
Arranque automatico	Si, por defecto desactivado		

Accesorios Compatible



KITDETKCC400

Kit for detergent (1l) and rinse aid (1l) storage for double wall models



KITSONLIV

Probe level kit for undercounter double wall models and hoodtype models



PHOOS02



RB40A3

Adapter for round basket for single wall models



RB40G01



WB40D01



WB40G03



WS4

Estructura inferior para lavavasos
400, 495x530x490 mm

Symbols glossary



HTR RINSING SYSTEM



MAX. LOAD HEIGHT 300mm



5 STAGE FILTER

Benefit (TT)

Balanced door

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integral double-skin

Thermal and acoustic insulation guaranteed

The double-skin design of undercounter dishwashers is engineered to optimise energy efficiency by minimising heat loss and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.