

UG515DSL-1

Familia	Lavavajillas
Subfamilia	Undercounter glasswashers
Dimensiones de la cesta	500x500 mm
Rinse pump	HTR system
Conexión eléctrica	400 V 3N~ / 12 A / 6,7 kW / 50 Hz



Distribución

Usuarios potenciales	Cafeterías - Vinotecas
-----------------------------	------------------------

Estética

Serie	Easyline	Color Led	Verde
--------------	----------	------------------	-------

Características técnicas

Water consumption per cycle	3,2 l	Dosificador de detergente peristáltico	Si, manual
Entrada de agua	5°C	Altura útil de carga	300 mm
Max. inlet temperature	60°C	Profundidad puerta abierta	925 mm
Dureza máxima del agua	54°f - 30°dH	Diámetro máximo de platos	300 mm
Entrada de agua	Frío 15°C	Product dimensions WxDxH	600x600x722 mm
Dosificador de detergente peristáltico	Si, manual		

Programas

Programs	6 programas automáticos; 1 programa completamente personalizable; Programas de autolimpieza
Program options	Aclarado extra; Ciclo de agua limpia
Máximo cesto / hora	51
Máximo platos / hora	1080

Conexión eléctrica

Tank heating element power	2000 W	Conexión por defecto	4800 W
Boiler heating element power	6000 W	Opción de conexión eléctrica	230 V 3~ / 21 A / 7,3 kW / 50 Hz; 230 V~ / 15 A / 3,4 kW / 50 Hz; 230 V~ / 20 A / 4,5 kW / 50 Hz; 230 V~ / 22 A / 5,0 kW / 50 Hz
Wash pump power	290 W		

Interface

Pantalla	8 dígitos	Alerta falta de detergente	Sí
Número de botones	5	Alerta de progreso del ciclo	Sí
Botón ON/OFF	Sí	Alerta de fin de ciclo	Sí
Alerta de sal	Sí	Diagnostico manual	Sí
Alerta de falta de abrillantador	Sí		

Construcción

Cuba	Profundidad del dibujo	Bomba de desagüe	Sí
Construcción de la cuba	Pared Doble	Capacidad de la cuba	11 l
Material de la cuba	Acero inoxidable AISI 304	Volumen del calderín	6.5 l
Panel trasero	Galvanizado	Ruido	Lpa 56,5 dBA
Puerta equilibrada	Sí	Clase de protección	IPX4
Filtro de la cuba	Acero inoxidable	Adjustable feet	Sí
Junta de la puerta	En 3 lados	Profundidad de carga	600 mm
Guías de estante	En relieve		

Equipo accesorios incluidos

Cesta plana	1x WB50G02	Tubo de desagüe	Si - 2m
Tubería de suministro de agua	Si - 1,5m		


Equipamiento

Bomba de desagüe	Sí	Option for auto daily switch on	Si, por defecto desactivado
Peristaltic detergent dispenser	Si, control electrónico	Contador de ciclos	Sí
Peristaltic rinse-aid dispenser	Si, control electrónico	Renovación parcial del agua en el tanque e incorporación bomba de drenaje	Sí
Descalcificador incorporado	Sí	Diámetro del tubo de entrada de agua	Si - 1,5m
Rinse boiler Thermostop system	Yes - default	Diámetro del tubo de desagüe	Si - 2m

Wash pump soft start system	Sì	Dosificador de detergente peristáltico	Si, manual
Stand-by system	Sì	Dosificador de detergente peristáltico	Si, manual

Datos logísticos

Ancho del producto empaquetado	660 mm	Dimensiones del producto embalado	890X660X700
Profundidad producto embalado	700 mm	Peso neto	59.000 kg
Altura del producto embalado	890 mm	Peso bruto (kg)	67.000



R	PANNELLO RETRO LOWER BACK PANEL
Q	MORSETTO EGUIPOTENZIALE EARTH TERMINAL
P	TUBI POMPE PERISTALTICHE PERISTALTIC HOSES
E	CAVO ALIMENTAZIONE ELETTRICA ELECTRICITY SUPPLY CABLE
S	TUBO DI SCARICO DRAIN HOSE
T	ENTRATA CAVO DI ALIMENTAZIONE DOSATORE ESTERNO EXTERNAL DISPENSER POWER CABLE ENTRY POINT
C	TUBO DI CARICO FILLER HOSE

Accesorios Compatible



KITSONLIV
Probe level kit



PB50D01
Cesta de polipropileno para 18 platos,
500x500x105 mm



PHOOS01



PHOOS02



WB50PG5
Wire basket with flat bottom for 25
plastic glasses, dim. (WxDxH)
500x500x260 mm



WH00S01



WS5
Estructura inferior para lavavasos 500,
595x595x490 mm

Symbols glossary



HTR RINSING SYSTEM



MAX. LOAD HEIGHT 300mm



5 STAGE FILTER

Benefit (TT)

Balanced door

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integrated softener

Effective water treatment for consistently sparkling glasses

The integrated continuous regeneration water softener ensures effective water treatment, enhancing washing performance and preserving the machine's operational lifespan. The resin regeneration process takes place during the wash cycle without interruptions, providing constant control over water hardness. This system prevents limescale buildup, maximises detergent efficiency, and guarantees spotless results on glassware and dishes.

Integral double-skin

Thermal and acoustic insulation guaranteed

The double-skin design of undercounter dishwashers is engineered to optimise energy efficiency by minimising heat loss and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.