

UM4545

Sink material Stainless steel

Type Side by side undermount bowls

No. of bowls 2

EAN code 8017709157357



Aesthetics



AestheticUniversaleBuilding in typeUndermountSeriesAlbaLogoEmbossedColourStainless steelTap hole / precut tapNo Taphole

Finishing Brushed hole

	Bowl type RH	Bowl thickness (mm)	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Traditional	0.6	450 x 400 x 180	180	80	Yes, traditional	Wall position	3.5"
LH Bowl	Traditional	0.6	450 x 400 x 180	180	80	Yes, traditional	Wall position	3.5"

Technical Features



Frame thickness 1 mm

Dimensions of the 180x890x510 mm

product (mm)

Cutout dimension 459*839 mm

undermount (mm)

Undermount cutout 5 mm

radius

Base unit size 90 cm

Tap hole diameter35 mmDividing wall width30 mm

Gasket type Sealing paste

No. of clips 8


Type of clips Undermount clip



Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories





Siphon double bowls sinks (dishwasher connection included)



DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



RND1V

Rondò waste kit 1 bowl with standard overflow



Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



Benefit (TT)

Two bowls

Two bowls for greater versatility and dual functionality