

# UW60132D

Family	Professional dishwasher
Subfamily	Utensilwasher
Type	Utensilwasher
Crockery	Utensils
Basket dimensions	600x1320 mm
Rinse pump	HTR system
Wash pump	Standard
Power connection	400 V 3N~ / 45 A / 18,6 kW /50 Hz



## Target

Solutions	Restaurants/Pubs; Bakery/Pastry making; Frozen bakery industry; Other food industry; Catering and Institutions
-----------	--

## Aesthetics

Led color	Red
-----------	-----

## Technical Features

Trays washing option	Yes	Rinse load	0,4 l/h
Water consumption per cycle	7,5	Usable load height	860 mm
Minimum water consumption per cycle	1,8 l	Height open door	2465 mm
Min. water connection temperature	5°C	Depth with open door	1255 mm
Max. inlet temperature	60°C	Maximum height no-basket wash	860 mm
Max water hardness	12°F - 7°dH	Product dimensions WxDxH	1450x860x2100 mm
Detergent load	1,5 l/h		

## Programs

Program table	Utensil washer
---------------	----------------

Utensil washers programs	Short - 2"; Long - 4"; Endless
Maximum basket/hour	30
Maximum dishes/hour	

## Electrical Connection

Plug	Not present	Wash pump power	3x2200W
Tank heating element power	6000 W	Default connection	18600 W
Boiler heating element power	12000 W	Optional electrical connection	230 V~ / 78,2 A / 18 kW / 50 Hz

## Interface

Display	4 digit	On/Off button	Yes
Number of buttons	3		

## Construction

Tank Construction	With printed base Single-skin	Filter	2-stage filter system
Tank material	Stainless steel AISI 304	Tank capacity	130 l
Back panel	Galvanized	Boiler capacity	17 l
Upper wash system	Two 3-arms wash and two split rinse spray arms, stainless steel	Noise	LpA<70 dB(A)
Lower wash system	Two 4-arms wash and two split rinse spray arms, stainless steel	Protection class	IPX4
Tank filter	Stainless steel	Adjustable feet	Yes
Rack guides	Welded	Drain max. height	950 mm

## Accessories included


Cutlery basket	1x WH00S02	Drain hose	Yes - 2m
Water supply hose	Yes - 2,5m		

## Equipments

Peristaltic detergent dispenser	Manual	Water supply pipe diameter	DN15 - ½"
Peristaltic rinse-aid dispenser	Manual	Drain supply pipe diameter	DN20-G 3/4"
Rinse boiler Thermostop system	Yes - default	Detergent (red) hose lenght	2,2m
Wash pump soft start system	Yes	Rinse aid (blue) hose lenght	2,2m
Break tank	Yes		

# Logistic Information


Width packed product	980 mm	Packed product dimensions	2230X980X1560
Depth packed product	1560 mm	Net weight	335.000 kg
Height packed product	2230 mm	Gross weight (kg)	376.000



D = SCARICO 1/2", VIDEANGE 1/2", DRAIN 1/2", ABFLUSS 1/2", DESAGÜE 1/2", CIBBB 1/2"  
C = CARICAMENTO ACQUA 1/2" GAS, CHARGEMENT EAU 1/2" GAZ, WATER INLET 1/2" GAS, ZUFLOSS 1/2" GAS, CARGA AGUA 1/2" GAS, НАПОР ВОДЫ 1/2" GAS  
E = ALLACCIAMENTO ELETTRICO, BRANCHEMENT ELECTRIQUE, ELECTRIC CONNECTION, ELEKTRISCHER ANSCHLUSS, CONEXION ELECTRICA, ЭЛЕКТРИЧЕСКОЕ ПОДКЛЮЧЕНИЕ

## Compatible Accessories

---

**WB60132G02**


Utensilwasher grid, dim. (WxDxH)  
1320x600 mm

**WB6070G01**

Universal basket with flat bottom,  
dim. (WxDxH) 700x600x305 mm

**WH00B02**

Block for sac à poche

**WH00S02**

Basket for utensils, dim. (WxDxH)  
150x150x250 mm

## Symbols glossary

---



SUITABLE FOR EURONORM TRAY



SUITABLE FOR GASTRONORM  
TRAY



HTR RINSING SYSTEM



MAX.USABLE HEIGHT 850mm

---

## Benefit (TT)

---

### Interface

Control panel with electronic buttons

The electronic control panel features an intuitive interface with soft-touch buttons, allowing easy selection of one of the three wash programmes: short, medium, or intensive. There are also buttons for power, selection, and cycle start. The display provides real-time monitoring of the tank and boiler temperature, as well as diagnostics, ensuring effortless and immediate control of the main functions.

### 2-stage system

Two-stage filtration system to ensure optimal washing performance and maximum water purity.

The filtration system is entirely made of AISI 304 stainless steel, ensuring maximum resistance, durability, and corrosion protection. It consists of two filtration stages: the first features a grid that prevents dirt residues from entering the tank, thereby avoiding water clouding; the second protects the washing pumps by retaining any debris that may accidentally enter the tank during filter cleaning.

### HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

### Door

Split and balanced doors for maximum ergonomics

The split and balanced doors have been designed with the aim of optimising ergonomics during tool loading and unloading operations. Their design allows for easier use, minimising the physical effort required from the operator. This helps improve work efficiency while also ensuring greater comfort and safety in the working environment.

### Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

### Wash pumps

Triple-pump washing system to effectively remove even the most stubborn dirt

The Smeg utensil washer is equipped with an innovative triple-pump washing system, designed to provide high power and an even distribution of water flow. This advanced technology ensures thorough and effective cleaning, removing even the most stubborn dirt residues.