

# VFU34SFR

Sink material Stainless steel Sink type Single-pressed bowl

No. of bowls

EAN code 8017709304638



### **Aesthetics**







Universal **Aesthetics** Colour Stainless steel **Finishing** Brushed

Series Mira **Building in type** 

Tap hole / precut tap

Flush fitted, Flat, Undermount **Embossed** No Taphole

hole

Logo

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	340 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

### **Technical Features**



Dimensions of the product WxDxH (mm) 200x382x442 mm

Height from kitchen top 1 mm Base unit size 45 cm No. of clips

Cutout dimension (mm) **Cutout dimension** 

370\*430 mm 344\*404 mm

Type of clips

Standard + undermount clip


undermount (mm) **Cutout radius** 17 mm

### **Accessories Included**



Accessories for installation

Strainer, Siphon with dishwasher outlet connection, Fixing clips, Silicone





# **Compatible Accessories**





Siphon single bowl sinks (dishwasher connection included)



#### 3713

Siphon double bowls sinks (dishwasher connection included)



#### CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



#### COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



#### COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



#### COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



#### **DB34**

Cestello in filo inox per abbinamento alle vasche di dimensione 340\*400 mm



#### **KITDS**

Soap dispenser Round knob



#### KITFD050

Waste disposal 0,5 HP Motor: 1/2 horsepower Fits all sinks with 3 1/2" waste outlet



#### KITFD075

Waste disposal 0,75 HP Motor: 3/4 horsepower Fits all sinks with 3 1/2" waste outlet



#### KITFD100

Waste disposal 1 HP Motor: 1 horsepower Fits all sinks with 3 1/2" waste outlet



#### RND1V

Rondò waste kit 1 bowl with standard overflow



# Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Flat: Installation of product with flat edge.



Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



# **Benefit**

#### One bowl

A single bowl for greater adaptability, capacity and space optimisation