

VFU34SFR

Sink materialStainless steelSink typeSingle-pressed bowl

No. of bowls

EAN code 8017709304638



Aesthetics



Aesthetics Universal Series Mira

Colour Stainless steel
Finishing Brushed

Building in type

Flush fitted, Flat, Undermount Embossed

LogoEmbossedTap hole / precut tapNo Taphole

hole

_	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	340 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

Technical Features



Dimensions of the product WxDxH (mm)

200x382x442 mm

Height from kitchen top 1 mm

Base unit size 45 cm

No. of clips 4

Cutout dimension (mm)
Cutout dimension

370*430 mm 344*404 mm

Type of clips

Standard + undermount clip


undermount (mm)
Cutout radius 17 mm

Accessories Included



Accessories for installation

Strainer, Siphon with dishwasher outlet connection, Fixing clips, Silicone





Not included accessories



RND1V

Rondò waste kit 1 bowl with standard overflow



KITFD050

Waste disposal 0,5 HP Motor: 1/2 horsepower Fits all sinks with 3 1/2" waste outlet



DB34

Cestello in filo inox per abbinamento alle vasche di dimensione 340*400 mm



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITFD100

Waste disposal 1 HP Motor: 1 horsepower Fits all sinks with 3 1/2" waste outlet



3712

Siphon single bowl sinks (dishwasher connection included)



3713

Siphon double bowls sinks (dishwasher connection included)



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



KITDS

Soap dispenser Round knob



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



KITFD075

Waste disposal 0,75 HP Motor: 3/4 horsepower Fits all sinks with 3 1/2" waste outlet



Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24.5



Flat: Installation of product with flat edge.



Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.

Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.