

VFU34SFR

Sink material

Type

No. of bowls

EAN code

Stainless steel

Monoblock bowl

1

8017709304638



Aesthetics



Aesthetic

Series

Colour

Finishing

Universale

Mira

Stainless steel

Brushed

Building in type

Logo

Tap hole / precut tap hole

Flush fitted, Flat, Undermount

Embossed

No Taphole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	340 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

Technical Features



Dimensions of the product (mm)

Cutout dimension topmount (mm)

Cutout dimension undermount (mm)

Undermount cutout radius

200x382x442 mm

370\*430 mm

344\*404 mm

17 mm

Height from kitchen top

Base unit size

No. of clips

Type of clips

1 mm

45 cm


4

Standard + undermount clip

Accessories Included

## Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Silicone



## Not included accessories



### RND1V

Rondò waste kit 1 bowl with standard overflow



### KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



### DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



### COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



### KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



### 3712

Siphon single bowl sinks (dishwasher connection included)



### 3713

Siphon double bowls sinks (dishwasher connection included)



### COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



### COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



### KITDS

Soap dispenser chrome finishing with round knob



### CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



### KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

---

## Symbols glossary (TT)

---



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Flat: Installation of product with flat edge.



Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.