

VFU50SFR

Sink materialStainless steelSink typeSingle-pressed bowl

No. of bowls

EAN code 8017709304669



Flush fitted, Flat,

Aesthetics







Aesthetics Universal
Colour Stainless steel
Finishina Brushed

Finishing Brushed
Series Mira

Building in type

Logo Embossed
Tap hole / precut tap No Taphole

hole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	500 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

Technical Features



Dimensions of the product WxDxH (mm)

Cutout dimension (mm)

200x540x440 mm

Height from kitchen top 1 mm
Base unit size 60 cm
No. of clips 8

Cutout dimension undermount (mm)

525*425 mm 504*404 mm

Type of clips

Standard + undermount clip


Cutout radius 17 mm

Accessories Included



Accessories for installation

Strainer, Siphon with dishwasher outlet connection, Fixing clips, Silicone





Compatible Accessories





Siphon single bowl sinks (dishwasher connection included)

30

3713

Siphon double bowls sinks (dishwasher connection included)



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



DB34

Cestello in filo inox per abbinamento alle vasche di dimensione 340*400 mm



KITDS

Soap dispenser Round knob



KITDSQ

Soap dispenser Square knob



KITFD050

Waste disposal 0,5 HP Motor: 1/2 horsepower Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP Motor: 3/4 horsepower Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP Motor: 1 horsepower Fits all sinks with 3 1/2" waste outlet



RND1V

Rondò waste kit 1 bowl with standard overflow



Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Flat: Installation of product with flat edge.



Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



Benefit

One bowl

A single bowl for greater adaptability, capacity and space optimisation