

VFU71SFR

Sink material Stainless steel Monoblock bowl Type

No. of bowls

EAN code 8017709304676



Aesthetics







Aesthetic Universale Colour Stainless steel

Finishing Brushed Series Mira

Building in type

Flush fitted, Flat, Undermount Logo **Embossed** Tap hole / precut tap No Taphole

hole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	710 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

Technical Features



Dimensions of the product (mm)

200x750x440 mm

Height from kitchen top 1 mm Base unit size 80 cm

Cutout dimension

735*425 mm

No. of clips Type of clips

Standard + undermount clip

topmount (mm) **Cutout dimension**

712*402 mm

undermount (mm) **Undermount cutout**

16 mm

radius


Accessories Included

SMEG SPA 2025/12/15



Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Silicone



SMEG SPA 2025/12/15



Compatible Accessories

3712



Siphon single bowl sinks (dishwasher connection included)

3713



Siphon double bowls sinks (dishwasher connection included)

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

COL19H



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

COL36



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm

DB34



St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth

KITDS



Soap dispenser chrome finishing with round knob

KITDSQ



Soap dispenser chrome finishing with square knob 40x40 mm

KITFD050

KITFD100



Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITFD075



Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

RND1V

Rondò waste kit 1 bowl with standard overflow

SMEG SPA 2025/12/15



Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Flat: Installation of product with flat edge.



Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.

SMEG SPA 2025/12/15



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

SMEG SPA 2025/12/15