

# VQR50RS

Sink material Stainless steel Welded bowl Type

No. of bowls 1

EAN code 8017709208974



### **Aesthetics**



Universale Building in type **Aesthetic** Ultra-low profile Series Mira Logo **Embossed** Colour Stainless steel Tap hole / precut tap 2 Tapholes

**Finishing** Brushed

hole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	500 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

### **Technical Features**



Dimensions of the 196x567x500 mm

product (mm)

**Cutout dimension** 545 x 470 mm

topmount (mm)

Height from kitchen top 6 mm

Base unit size 60 cm Tap hole 2

Tap hole diameter 35 mm Popup command Yes, single Popup command type Squared No. of clips 10


Type of clips Standard

# Accessories included



Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Gasket, Automatic pop - up with roudn rotary control





# **Compatible Accessories**





Siphon single bowl sinks (dishwasher connection included)

# 7

3713

Siphon double bowls sinks (dishwasher connection included)

#### CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



CB28QU

Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm





St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



**DB34** 

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITSLTRND1

Bowl automatic pop up Rondò waste kit with rectangular overflow and round knob



**STABMIX** 

Tap stabiliser



# Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24.5



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



# Benefit (TT)

### One bowl

A single bowl for greater adaptability, capacity and space optimisation

### Double tap hole

The sink is easily reversible, making it possible to create any type of kitchen composition

### Pop-up command

The pop-up command allows the sink drain to be opened and closed remotly with a simple gesture and without the need to touch the plug directly, increasing convenience and hygiene in the kitchen

### Tap hole

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area