

# VR12S4040

**Sink material** Stainless steel  
**Type** Welded bowl  
**No. of bowls** 2  
**EAN code** 8017709308131



## Aesthetics



<b>Aesthetic</b>	Universale	<b>Building in type</b>	Flush fitted, Flat, Undermount
<b>Colour</b>	Stainless steel	<b>Logo</b>	Embossed
<b>Finishing</b>	Brushed	<b>Tap hole / precut tap hole</b>	No Taphole
<b>Series</b>	Mira		

	Bowl type RH	Bowl thickness (mm)	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Minimum radius	1	400 x 400 x 200	200	12	Yes, flush fitted	Wall position	3.5"
LH Bowl	Minimum radius	1	400 x 400 x 200	200	12	Yes, flush fitted	Wall position	3.5"

## Technical Features



<b>Frame thickness</b>	1 mm	<b>Base unit size</b>	90, 100 cm
<b>Dimensions of the product (mm)</b>	201x840x440 mm	<b>Dividing wall width</b>	25 mm
<b>Cutout dimension topmount (mm)</b>	830x430 mm	<b>No. of clips</b>	10
<b>Cutout dimension undermount (mm)</b>	800x400 mm	<b>Type of clips</b>	Standard + undermount clip
		<b>Possibility to install waste disposal</b>	No

Undermount cutout radius 12 mm  
 Height from kitchen top 1 mm


## Accessories included



Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Silicone

Integrated flush waste kit Yes



---

## Compatible Accessories

---



### CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



### COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



### COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



### CB28QU

Single HPL chopping board for minimum radius, oak, measures 280 x 418 H 12 mm



### COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm











### KITPUSH

1 Bowl automatic pop up in AISI304 with push button ONLY for integrated waste kit bowls R12

---

## Symbols glossary

---

	Cupboard width required for sink installation.		Cupboard width required for sink installation.
	Sink depth - depending on the model, the depth can be from 13 to 24,5.		Flat: Installation of product with flat edge.
	Flush-fitted installation: Models of sinks/hobs which are integrated flush with the tabletop of a kitchen unit.		Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.
	A unique waste kit totally integrated with the sink gives an elegant effect and guarantees greater hygiene with the continuous surface allowing you to combine convenience with total safety during the food preparation. The new plug design is ergonomic and it's easier to extract.		On this sink it is not possible to install the waste disposal