

# VSGX860CT

Composite Sink material Composite bowl Type

No. of bowls

EAN code 8017709282387



### **Aesthetics**



**Aesthetic** Universale Applied Logo Alternative colours Colour Cement / Concrete Black, White

available Series Quadra

Tap hole / precut tap Prepared Building in type Standard

hole

Bowl Bowl Bowl dimensions, Radius corner right Strainer Strainer Overflow depth type RH WxDxH (mm) bowl (mm) position dimension (mm) RHMinimum Yes, flush Wall 796 x 386 x 215 215 6 3.5" Bowl radius fitted position

### **Technical Features**













Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant, Impact resistant, UV

Resistant

Base unit size 90 cm Tap hole 1 Tap hole diameter 35 mm No. of clips

Type of clips

Standard

Frame depth (mm) 5

Dimensions of the product (mm)

215x860x510 mm



Cutout dimension topmount (mm)

840 x 480 mm

Undermount cutout radius

15 mm

Height from kitchen top

10 mm


### Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips

Oak HPL chopping board

Yes





### **Compatible Accessories**

### CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

#### COL36



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm

## KITFD050



Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

#### KITFD100



Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



#### COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

#### **KITDSQ**



Soap dispenser chrome finishing with square knob 40x40 mm

## KITFD075



Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



# Alternative products

VSGX860MN



Colour: Black



## Symbols glossary



Cupboard width required for sink installation.



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets.



Antiscratch



High temperatures resistant



Easy to clean



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Antibacterial



Termal schock resistant



Impact resistant



UV protection, does not fade over time.