

VSGX860MN

Sink material Composite Type Composite bowl

No. of bowls

EAN code 8017709311735



Aesthetics



Universale **Aesthetic** Logo Applied

Series Quadra Alternative colours Cemento / Concrete

available Colour Black

Tap hole / precut tap Prepared Building in type Standard

hole

	Bowl type RH	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Minimum radius	796 x 386 x 215	215	6	Yes, flush fitted	Wall position	3.5"

Technical Features











5





Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant, Impact resistant, UV

Resistant

Base unit size 90 cm Tap hole 1 Tap hole diameter 35 mm No. of clips Standard

Type of clips

Frame depth (mm)

Dimensions of the product (mm)

215x860x510 mm

SMEG SPA 8/10/2025



Cutout dimension topmount (mm)

840 x 480 mm

Height from kitchen top

10 mm

Accessories included

Accessories for installation

Colander

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips

Yes


Black matt standard waste kit and rectangular overflow

Black HPL chopping

board

Yes

Yes



SMEG SPA 8/10/2025



Compatible Accessories



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

SMEG SPA 8/10/2025



Alternative products

VSGX860CT

Colour: Cement / Concrete



SMEG SPA 8/10/2025



Symbols glossary



Antibacterial



Cupboard width required for sink installation.



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets.



Termal schock resistant



Impact resistant



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Easy to clean



High temperatures resistant



UV protection, does not fade over time.

SMEG SPA 8/10/2025