

VSGX860N

Sink material Composite Type Composite bowl

No. of bowls

EAN code 8017709282394



Aesthetics



Universale **Aesthetic** Logo Applied

Series Quadra Alternative colours White, Cemento / Concrete available Colour Black

Tap hole / precut tap Building in type Standard

hole

Prepared

	Bowl type RH	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Minimum radius	796 x 386 x 215	215	6	Yes, flush fitted	Wall position	3.5"

Technical Features















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant, Impact resistant, UV

Resistant

Base unit size 90 cm Tap hole 1 Tap hole diameter 35 mm

No. of clips Type of clips Standard

Frame depth (mm) 5

Dimensions of the product (mm)

215x860x510 mm

SMEG SPA 15/12/2024



Cutout dimension topmount (mm)

840 x 480 mm

Undermount cutout

15 mm

radius

Height from kitchen top 10 mm


Accessories Included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips

Oak HPL chopping board

Yes



SMEG SPA 15/12/2024



Not included accessories



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

SMEG SPA 15/12/2024



Symbols glossary (TT)



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



Antiscratch



High temperatures resistant



Easy to clean



Sink depth - depending on the model, the depth can be from 13 to 24,5



Antibacterial



Termal schock resistant



Impact resistant



UV protection, does not fade over time.

SMEG SPA 15/12/2024