

VSTR3434-2

Sink material Stainless steel

Type Side by side undermount bowls

No. of bowls 2

EAN code 8017709190576



Aesthetics



AestheticUniversaleBuilding in typeUndermountColourStainless steelLogoEmbossedFinishingBrushedTap hole / precut tapNo Taphole

Series Mira hole

	Bowl type RH	Bowl thickness (mm)	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Minimum radius	1	340 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"
LH Bowl	Minimum radius	1	340 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

Technical Features



Frame thickness 1 mm

200x802x472 mm

Tap hole diameter Dividing wall width

Type of clips

35 mm 48 mm

product (mm) Cutout dimension

411*740 mm

No. of clips

8 Undermount clip

undermount (mm)

Dimensions of the


Base unit size 90 cm

Accessories included



Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories

3713



Siphon double bowls sinks (dishwasher connection included)

DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



RND1V

Rondò waste kit 1 bowl with standard overflow



Symbols glossary



Cupboard width required for sink installation.



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.